

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 035 198 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
13.09.2000 Bulletin 2000/37

(51) Int Cl.7: C11D 17/00, C11D 3/50,
C11D 3/12, C11D 3/20
// C11D3/36

(21) Application number: 99870081.9

(22) Date of filing: 30.04.1999

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

- Cunningham, Philip Andrew
Newcastle upon Tyne, NE12 9JN (GB)
- Green, Michael (NMN)
Newcastle upon Tyne, NE5 4SX (GB)
- McRitchie, Allan Campbell
Tyne & Wear, NE26 1SY (GB)

(30) Priority: 12.03.1999 EP 99870044

(71) Applicant: THE PROCTER & GAMBLE COMPANY
Cincinnati, Ohio 45202 (US)

(74) Representative: Gault, Nathalie et al
BVBA Procter & Gamble Europe Sprl
Temseleaan 100
1853 Strombeek-Bever (BE)

(72) Inventors:
• Arnau, José (NMN)
78180 Montigny-le-Bretonneux (FR)

(54) **Perfumed detergent tablet**

(57) The present invention relates to a perfumed detergent tablet, the tablet comprising a clay mineral com-

ponent, and the perfume comprising less than 0.6% of Schiff-base by weight of the perfume composition.

EP 1 035 198 A2

Description

Technical field of the invention

[0001] The present invention relates to perfumed detergent tablets, especially those adapted for use in washing machines, and to processes for making such tablets.

Background of the invention

[0002] Perfumed products are well-known in the art. However, consumer acceptance of such perfumed products like laundry and cleaning products is determined not only by the performance achieved with these products but also by the aesthetics associated therewith. The perfume components are therefore an important aspect of the successful formulation of such commercial products.

[0003] In addition, a clay mineral compound is a desirable ingredient of such laundry and cleaning product, in particular those products which are in tablet form. Indeed, the clay can provide softening benefit but can also serve as a disintegrant of such detergent tablets.

[0004] However, a problem encountered with perfumed detergent tablets containing a clay mineral compound is that the clay can have a detrimental effect on the performance of the perfume contained therein. Hence, not to be bound by theory, it is believed that due to the close physical proximity given by the tablet, the perfume is absorbed into the clay where it can interact with heavy metal ions and acid or base sites within the clay which as result may cause a discoloration of the clay. Still, the interaction between the perfume and the clay may also result in the tablet having a less attractive odour.

[0005] Accordingly, it is an object of the invention to provide a perfumed detergent tablet comprising a clay mineral compound which exhibit good perfume performance with reduced discoloration of the clay.

[0006] Further, cleaning compositions in tablet form have often been proposed, however these have not (with the exception of soap bars for personal washing) gained any substantial success, despite the several advantages of products in a unit dispensing form. One of the reasons for this may be that detergent tablets require a relatively complex manufacturing process. In particular, it is often desirable to provide the tablet with a coating and this adds to the difficulties of manufacture.

[0007] While tablets without a coating are entirely effective in use, they usually lack the necessary surface hardness to withstand the abrasion that is a part of normal manufacture, packaging and handling. The result is that non-coated tablets suffer from abrasion during these processes, resulting in chipped tablets and loss of active material.

[0008] Finally, coating of tablets is often desired for aesthetic reasons, to improve the outer appearance of the tablet or to achieve some particular aesthetic effect.

[0009] Numerous methods of tablet coating have been proposed, and many of these have been suggested for detergent tablets. However, all of these methods have certain disadvantages, as will be explained below.

[0010] GB-A-0 989 683, published on 22nd April 1965, discloses a process for preparing a particulate detergent from surfactants and inorganic salts; spraying on water-soluble silicate; and pressing the detergent particles into a solid form-retaining tablet. Finally, a readily water-soluble organic film-forming polymer (for example, polyvinyl alcohol) provides a coating to make the detergent tablet resistant to abrasion and accidental breakage.

[0011] EP-A-0 002 293, published on 13th June 1979, discloses a tablet coating comprising hydrated salt such as acetate, metaborate, orthophosphate, tartrate, and sulphate.

[0012] EP-A-0 716 144, published on 12th June 1996, also discloses laundry detergent tablets with water-soluble coatings which may be organic polymers including acrylic/maleic co-polymer, polyethylene glycol, PVPVA, and sugar.

[0013] WO9518215, published on 6th July 1995, provides water-insoluble coatings for solid cast tablets. The tablets are provided with hydrophobic coatings including wax, fatty acid, fatty acid amides, and polyethylene glycol.

[0014] EP-A-0 846 754, published on the 10th of June 1998, provides a tablet having a coating comprising a dicarboxylic acid, the coating material typically having a melting point of from 40°C to 200°C.

[0015] EP-A-0 846 755, published on the 10th of June 1998, provides a tablet having a coating comprising a material insoluble in water at 25°C, such as C12-C22 fatty acids, adipic acid or C8-C13 dicarboxylic acids.

[0016] EP-A-0 846 756, published on the 10th of June 1998, provides a tablet having a coating comprising a disintegrant material and preferably an effervescent material.

[0017] Recently, it has been found means by which coated tablets can be provided with a coating so that they can be stored, shipped and handled without damage, the coating being easily broken when the tablet is in the washing machine, releasing the active ingredients into the wash solution. Typical of such disclosure can be found in pending European patent applications EP 99870017.3, EP 99870018.1, and EP 99870019.9.

[0018] However, whilst giving satisfactory results, it has now been found that where a clay mineral compound is present in the coating of the detergent tablet, the clay, for the same believed reasons stated above, can have a detri-

mental effect on the performance of the perfume contained therein as well as on the appearance of the coating, i.e. discoloration of the coating.

[0019] These problems have further been found more acute overtime, and more particularly where the coating also comprises an acid having a melting point of at least 40°C, more particularly with a melting point of at least 145°C.

[0020] Accordingly, the detergent formulator is also faced with the problems of providing a coated tablet having a coating which has satisfactory appearance, is sufficiently hard to protect the tablet from mechanical forces when stored, shipped and handled, and disperses readily in an aqueous solution whilst still giving satisfactory perfume performance.

[0021] Further, the perfuming of detergent tablet is a concern to the detergent formulator. Hence, the presence of the coating on the tablet can reduce the diffusion of the perfume from the tablet resulting in a less attractive odour.

[0022] It has now surprising been found that perfume compositions which contain less than 0.6 % by weight of the perfume of Schiff Base in a detergent tablet overcomes these problems. Such a finding is surprising because Schiff bases which are generally known to have a yellow colouration to start with, were not expected to give rise to the discolouration of the clay, especially over time.

Summary of the Invention

[0023] The present invention is a perfumed detergent tablet, the tablet comprising a clay mineral compound; and wherein the perfume comprises less than 0.6% of Schiff-base by weight of the perfume composition.

[0024] By "perfumed detergent tablet", it is meant that the perfume can be present in the coating if present, or in the detergent composition, or both.

Detailed Description of the Invention

Clay

[0025] An essential ingredient of the detergent tablet is a clay. The clay may be present in any of the detergent composition, the coating if present, or both.

[0026] By clay mineral compound (or in abbreviation, "clay"), it is meant herein a hydrous phyllosilicate, typically having a two or three layer crystal structure. For clarity, it is noted that the term clay mineral compound, as used herein, excludes sodium aluminosilicate zeolite builder compounds, which however, may be included in the compositions of the invention as optional components. Further description of clays may be found in Kirk-Othmer, Encyclopaedia of Chemical Technology, 4th edition, Volume 6, page 381, as published by John Wiley and Sons.

[0027] The clay mineral compound is preferably a smectite clay compound. Smectite clays are disclosed in the US Patents No.s 3,862,058, 3,948,790, 3,954,632 and 4,062,647 and European Patents No.s EP-A-299,575 and EP-A-313,146 all in the name of the Procter and Gamble Company.

[0028] The term smectite clays herein includes both the clays in which aluminium oxide is present in a silicate lattice and the clays in which magnesium oxide is present in a silicate lattice. Typical smectite clay compounds include the compounds having the general formula $Al_2(Si_2O_5)_2(OH)_2 \cdot nH_2O$ and the compounds having the general formula $Mg_3(Si_2O_5)_2(OH)_2 \cdot nH_2O$. Smectite clays tend to adopt an expandable three layer structure.

[0029] Specific examples of suitable smectite clays include those selected from the classes of the montmorillonites, hectorites, volchonkoites, nontronites, saponites and sauconites, particularly those having an alkali or alkaline earth metal ion within the crystal lattice structure. Sodium or calcium montmorillonite are particularly preferred.

[0030] Suitable smectite clays, particularly montmorillonites, are sold by various suppliers including English China Clays, Laviosa, Fordamin, Georgia Kaolin and Colin Stewart Minerals (CSM).

[0031] Preferred smectite clays are sold under the tradename of White Bentonite STP by Fordamin and Detercal P7 by Laviosa Chemical Minería SPA.

[0032] Clays for use herein may be subjected to an acid washing treatment with any suitable mineral or organic acid. Such clays give rise to an acid pH on dissolution in distilled water. A commercially available "acid clay" of this type is sold under the tradename Tonsil P by Sud Chemie AG.

[0033] Substitution of small cations, such as protons, sodium ions, potassium ions, magnesium ions and calcium ions, and of certain organic molecules including those having positively charged functional groups can typically take place within the crystal lattice structure of the smectite clays. A clay may be chosen for its ability to preferentially absorb one cation type, such ability being assessed by measurements of relative ion exchange capacity. The smectite clays suitable herein typically have a cation exchange capacity of at least 50 meq/100g. U.S. Patent No. 3,954,632 describes a method for measurement of cation exchange capacity.

[0034] The crystal lattice structure of the clay mineral compounds may have, in a preferred execution, a cationic fabric softening agent substituted therein. Such substituted clays have been termed "hydrophobically activated" clays. The cationic fabric softening agents are typically present at a weight ratio, cationic fabric softening agent to clay, of

from 1:200 to 1:10, preferably from 1:100 to 1:20. Suitable cationic fabric softening agents include the water insoluble tertiary amines or long chain amide materials as disclosed in GB-A-1 514 276 and EP-B-0 011 340.

[0035] A preferred commercially available "hydrophobically activated" clay is a bentonite clay containing approximately 40% by weight of a dimethyl ditallow quaternary ammonium salt sold under the tradename Claytone EM by English China Clays International.

[0036] Preferably, the clay which is present in the detergent composition is present in an intimate mixture or in a particle with a humectant and a hydrophobic compound, preferably a wax or oil, such as paraffin oil. Preferred humectants are organic compounds, including propylene glycol, ethylene glycol, dimers or trimers of glycol, most preferably glycerol. The particle is preferably an agglomerate. Alternatively, the particle may be such that the wax or oil and optionally the humectant form an encapsulate on the clay or alternatively, the clay be an encapsulate for the wax or oil and the humectant. It may be preferred that the particle comprises an organic salt or silica or silicate.

[0037] In another embodiment, the clay in the detergent composition is preferably mixed with one or more surfactants and optionally builders and optionally water, in which case the mixture is preferably subsequently dried. Preferably, such a mixture is further processed in a spray-drying method to obtain a spray dried particle comprising the clay.

[0038] It may also be preferred that the intimate mixture comprises a chelating agent.

[0039] Depending on its end use, the clay will preferably be present in different particles size. Hence, when softening is desired, it is preferred that at least 50% by weight, preferably substantially all (e.g. at least 90% or 95%) by weight of the clay is present as granules. By granules, it is meant that the particles of the clay mineral compound which is present in the detergent composition are included as components of agglomerate particles optionally containing other detergent compounds. Where present as such components, the term "largest particle dimension" of the clay mineral compound refers to the largest dimension of the clay mineral component as such, and not to the agglomerated particle as a whole. Typically, the granules will have a particle size of at least 100 micrometers, generally 100-1700 micrometers.

[0040] When a coating is present, it is often desired to have a clay as disintegrant in the coating. In this instance, the clay is preferably present in the coating, having a particle size of less than 75 µm, more preferably of less than 53 µm.

[0041] Preferably, the tablet is a softening tablet. By softening tablet, it is meant that the level of clay will typically be of at least 5%, preferably at least 8%, and most preferably at least 10% by weight of the tablet. The amount may be less than 25%, usually less than 20%, and preferably not more than 15% by weight of the tablet.

Perfume

[0042] The tablets of the present invention also comprises a perfume composition, that being either present in the coating if present, or in the detergent composition, or even in both the coating and the detergent composition. Suitable perfumes herein include materials which provide an olfactory aesthetic benefit such as to make such tablets more aesthetically pleasing to the consumer, imparting a pleasant fragrance to fabrics treated therewith and/or cover any "chemical" odor that the product may have.

[0043] As used herein, perfume includes fragrant substance or mixture of substances including natural (i.e., obtained by extraction of flowers, herbs, leaves, roots, barks, wood, blossoms or plants), artificial (i.e., a mixture of different nature oils or oil constituents) and synthetic (i.e., synthetically produced) odoriferous substances. Such materials are often accompanied by auxiliary materials, such as fixatives, extenders, stabilizers and solvents. These auxiliaries are also included within the meaning of "perfume", as used herein. Typically, perfumes are complex mixtures of a plurality of organic compounds.

[0044] For the purpose of the present invention, the perfume composition contains less than 0.6% by weight of the perfume composition of Schiff-base. The perfume for use herein is used at levels of up to 5 grams per tablet and preferably is substantially free of Schiff-Base.

[0045] By "substantially free", it is meant that the perfume composition comprises less than 0.4 % by weight of Schiff Base, and more preferably is free of Schiff Base.

[0046] Schiff-Bases are the condensation of an aldehyde perfume ingredient with an anthranilate. A typical description can be found in US 4853369. The Schiff Bases can be added directly to the perfume composition or can be formed in situ in the perfume composition by adding to it an Anthranilate such as Methyl or Ethyl Anthranilate along with an aldehyde which can react with the Anthranilate to form the Schiff Base.

[0047] Not to be bound by theory, it is believed that when this compound comes in contact with the clay it can undergo reactions most likely catalysed by the metal ions present in the clay and that these reactions produce more highly coloured by-products.

[0048] Typical of Schiff bases are selected from Schiffs base of 4-(4-hydroxy-4-methylpentyl)-3-cyclohexene-1-carboxaldehyde and methyl anthranilate; condensation products of hydroxycitronellal and methyl anthranilate; 4-(4-hydroxy-4-methyl pentyl)-3-cyclohexene-1-carboxaldehyde and methyl anthranilate; Methyl Anthranilate and Hydroxycitronellal commercially available under the tradename Aurantol; Methyl Anthranilate and Methyl Nonyl Acetaldehyde commercially available under the tradename Agrumea; Methyl Anthranilate and PT Bucinal commercially available

under the tradename Verdantol; Methyl anthranilate and Lyril commercially available under the tradename Lyrane; Methyl Anthranilate and Ligustral commercially available under the tradename Ligantral; and mixtures thereof.

[0049] Preferably, the perfume composition is free of perfume ingredients selected from Methyl Anthranilate and Hydroxycitronellal commercially available under the tradename Auranlio; Methyl Anthranilate and Methyl Nonyl Acetaldehyde commercially available under the tradename Agrumea; Methyl Anthranilate and PT Bucinal commercially available under the tradename Verdantol; Methyl anthranilate and Lyril commercially available under the tradename Lyrane; Methyl Anthranilate and Ligustral commercially available under the tradename Ligantral; and mixtures thereof.

[0050] Of course, the perfume composition will contain one or more perfume ingredients. Suitable perfume ingredients are disclosed in U.S. Pat. 5,500,138, said patent being incorporated herein by reference.

[0051] Examples of perfume ingredients useful in the perfume compositions include, but are not limited to, hexyl cinnamic aldehyde; amyl cinnamic aldehyde; amyl salicylate; hexyl salicylate; terpineol; 3,7-dimethyl-*cis*-2,6-octadien-1-ol; 2,6-dimethyl-2-octanol; 2,6-dimethyl-7-octen-2-ol; 3,7-dimethyl-3-octanol; 3,7-dimethyl-*trans*-2,6-octadien-1-ol; 3,7-dimethyl-6-octen-1-ol; 3,7-dimethyl-1-octanol; 2-methyl-3-(para-*tert*-butylphenyl)-propionaldehyde; 4-(4-hydroxy-4-methylpentyl)-3-cyclohexene-1-carboxaldehyde; tricyclodecanyl propionate; tricyclodecanyl acetate; anisaldehyde; 2-methyl-2-(para-*iso*-propylphenyl)propionaldehyde; ethyl-3-methyl-3-phenyl glycidate; 4-(para-hydroxyphenyl)butan-2-one; 1-(2,6,6-trimethyl-2-cyclohexen-1-yl)-2-buten-1-one; para-methoxyacetophenone; para-methoxy- α -phenylpropene; methyl-2-*n*-hexyl-3-oxo-cyclopentane carboxylate; undecalactone gamma.

Additional examples of fragrance materials include, but are not limited to, orange oil; lemon oil; grapefruit oil; bergamot oil; clove oil; dodecalactone gamma; methyl-2-(2-pentyl-3-oxo-cyclopentyl) acetate; beta-naphthol methyl ether; methyl-beta-naphthylketone; coumarin; decylaldehyde; benzaldehyde; 4-*tert*-butylcyclohexyl acetate; alpha, alpha-dimethylphenethyl acetate; methylphenylcarbinyl acetate; cyclic ethyleneglycol diester of tridecanoic acid; 3,7-dimethyl-2,6-octadiene-1-nitrile; ionone gamma methyl; ionone alpha; ionone beta; petitgrain; methyl cedrylone; 7-acetyl-1,2,3,4,5,6,7,8-octahydro-1,1,6,7-tetramethyl-naphthalene; ionone methyl; methyl-1,6,10-trimethyl-2,5,9-cyclododecatrien-1-yl ketone; 7-acetyl-1,1,3,4,4,6-hexamethyl tetralin; 4-acetyl-6-*tert*-butyl-1,1,10-trimethyl indane; benzophenone; 6-acetyl-1,1,2,3,3,5-hexamethyl indane; 5-acetyl-3-isopropyl-1,1,2,6-tetramethyl indane; 1-dodecanal; 7-hydroxy-3,7-dimethyl octanol; 10-undecen-1-ol; isohexenyl cyclohexyl carboxaldehyde; formyl tricyclodecan; cyclopentadecan-olide; 16-hydroxy-9-hexadecenoic acid lactone; 1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylcyclopentene-gamma-2-benzopyrane; ambroxane; dodecanhydro-3a,6,6,9a-tetramethylnaphtho[2,1,b]furan; cedrol; 5-(2,2,3-trimethylcyclopent-3-enyl)-3-methylpentan-2-ol; 2-ethyl-4-(2,2,3-trimethyl-3-cyclopenten-1-yl)-2-buten-1-ol; caryophyllene alcohol; cedryl acetate; para-*tert*-butylcyclohexyl acetate; patchouli; oilibanum resinoid; labdanum; vetiver; copaiba balsam; fir balsam; hydroxycitronellal and indol; phenyl acetaldehyde and indol.

[0052] More examples of perfume components are geraniol; geranyl acetate; linalool; linalyl acetate; tetrahydrolinalool; citronellol; citronellyl acetate; dihydromyrcenol; dihydromyrcenyl acetate; tetrahydromyrcenol; terphenyl acetate; nopol; nopol acetate; 2-phenylethanol; 2-phenylethyl acetate; benzyl alcohol; benzyl acetate; benzyl salicylate; benzyl benzoate; styrallyl acetate; dimethylbenzylcarbinol; trichloromethylphenylcarbinyl methylphenylcarbinyl acetate; isononyl acetate; vetiveryl acetate; vetiverol; 2-methyl-3-(*p*-*tert*-butylphenyl)-propanal; 2-methyl-3-(*p*-isopropylphenyl)-propanal; 3-(*p*-*tert*-butylphenyl)-propanal; 4-(4-methyl-3-pentenyl)-3-cyclohexenecarbaldehyde; 4-acetoxy-3-pentyltetrahydropyran; methyl dihydrojasmonate; 2-*n*-heptylcyclopentanone; 3-methyl-2-pentylcyclopentanone; *n*-decenal; *n*-dodecanal; 9-decenol-1; phenoxethyl isobutyrate; phenylacetaldehyde dimethylacetal; phenylacetaldehyde diethylacetal; geranonitrile; citronellonitrile; cedryl acetate; 3-*isocampyl*cyclohexanol; cedryl methyl ether; isolongifolanone; aubepine nitrile; aubepine; heliotropine; eugenol; vanillin; diphenyl oxide; hydroxycitronellal ionones; methyl ionones; isomethyl ionones; ionones; *cis*-3-hexenol and esters thereof; indane musk fragrances; tetralin musk fragrances; isochroman musk fragrances; macrocyclic ketones; macrocyclic musk fragrances; ethylene brassylate.

[0053] The perfumes useful in the present invention compositions are substantially free of halogenated materials and nitromusks.

[0054] Suitable solvents, diluents or carriers for perfumes ingredients mentioned above are for examples, ethanol, isopropanol, diethylene glycol, monoethyl ether, dipropylene glycol, diethyl phthalate, triethyl citrate, etc. The amount of such solvents, diluents or carriers incorporated in the perfumes is preferably kept to the minimum needed to provide a homogeneous perfume solution.

[0055] Tablets of the present invention as well as coated tablets according to the invention provide improved fabric perfume deposition.

[0056] Preferably, the perfume composition is present in an amount of 0.001% to 10%, preferably from 0.005% to 5%, more preferably from 0.01% to 3%, and even more preferably from 0.02% to 2% by weight of the tablet.

[0057] The perfume can be incorporated to the tablet by any conventional means known to the skilled person. One preferred means is by spray-on of the perfume composition onto the tablet.

Heavy metal ions sequestrants

[0058] The perfumed detergent tablets of the invention preferably also contain as an optional component a heavy metal ion sequesterant composition, that being either present in the coating if present, or in the detergent composition, or even in both the coating and the detergent composition. By heavy metal ion sequesterant, it is meant herein components which act to sequester (chelate) heavy metal ions. These components may also have calcium and magnesium chelation capacity, but preferentially they show selectivity to binding heavy metal ions such as iron, manganese and copper.

[0059] Heavy metal ion sequestrants are generally present at a level of from 0.005% to 20%, preferably from 0.1% to 10%, more preferably from 0.25% to 7.5% and most preferably from 0.5% to 5% by weight of the tablet.

[0060] Heavy metal ion sequestrants, which are acidic in nature, having for example phosphonic acid or carboxylic acid functionalities, may be present either in their acid form or as a complex/salt with a suitable counter cation such as an alkali or alkaline metal ion, ammonium, or substituted ammonium ion, or any mixtures thereof. Preferably any salts/complexes are water soluble. The molar ratio of said counter cation to the heavy metal ion sequesterant is preferably at least 1:1.

[0061] Suitable heavy metal ion sequestrants for use herein include organic phosphonates, such as the amino alkylene poly (alkylene phosphonates), alkali metal ethane 1-hydroxy diphosphonates and nitrilo trimethylene phosphonates.

[0062] Preferred among the above species are diethylene triamine penta (methylene phosphonate), ethylene diamine tri (methylene phosphonate) hexamethylene diamine tetra (methylene phosphonate) and hydroxy-ethylene 1,1 diphosphonate.

[0063] Other suitable heavy metal ion sequesterant for use herein include nitrilotriacetic acid and polyaminocarboxylic acids such as ethylenediaminetetraacetic acid, ethylenetriamine pentacetic acid, ethylenediamine disuccinic acid, ethylenediamine diglutaric acid, 2-hydroxypropylenediamine disuccinic acid or any salts thereof.

[0064] Especially preferred is ethylenediamine-N,N'-disuccinic acid (EDDS) or the alkali metal, alkaline earth metal, ammonium, or substituted ammonium salts thereof, or mixtures thereof. Preferred EDDS compounds are the free acid form and the sodium or magnesium salt or complex thereof. Examples of such preferred sodium salts of EDDS include Na_2EDDS and Na_3EDDS . Examples of such preferred magnesium complexes of EDDS include MgEDDS and Mg_2EDDS .

[0065] Other suitable heavy metal ion sequestrants for use herein are iminodiacetic acid derivatives such as 2-hydroxyethyl diacetic acid or glyceryl imino diacetic acid, described in EP-A-317,542 and EP-A-399,133.

[0066] The iminodiacetic acid-N-2-hydroxypropyl sulfonic acid and aspartic acid N-carboxymethyl N-2-hydroxypropyl-3-sulfonic acid sequestrants described in EP-A-516,102 are also suitable herein. The β -alanine-N,N'-diacetic acid, aspartic acid-N,N'-diacetic acid, aspartic acid-N-monoacetic acid and iminodisuccinic acid sequestrants described in EP-A-509,382 are also suitable.

[0067] EP-A-476,257 describes suitable amino based sequestrants. EP-A-510,331 describes suitable sequestrants derived from collagen, keratin or casein. EP-A-528,859 describes a suitable alkyl iminodiacetic acid sequesterant. Dipicolinic acid and 2-phosphonobutane-1,2,4-tricarboxylic acid are also suitable. Glycinamide-N,N'-disuccinic acid (GADS), ethylenediamine-N,N'-diglutaric acid (EDDG) and 2-hydroxypropylenediamine-N,N'-disuccinic acid (HPDDS) are also suitable.


[0068] Most preferred heavy metal ion sequestrants for use herein is alkali metal ethane 1-hydroxy diphosphonates, in particular when used in combination with diethylene triamine penta (methylene phosphonate). Most preferably, the heavy metal ion sequesterant is present in the coating.

Detergent ingredients

[0069] The tablets may comprise components such as surfactants, enzymes, detergent etc.... Typical tablet compositions for the preferred embodiment of the present invention are disclosed in the pending European applications of the Applicant n° 96203471.6, 96203482.5, 96203473.2 and 96203464.1 for example. Elements typically entering in the composition of detergent tablets or of other forms of detergents such as liquids or granules are detailed in the following paragraphs.

Detergent surfactants

[0070] Surfactants are typically comprised in a detergent composition. The dissolution of surfactants is favoured by the addition of the highly soluble compound. Nonlimiting examples of surfactants useful herein typically at levels from about 1% to about 55%, by weight, include the conventional C_{11} - C_{18} alkyl benzene sulfonates ("LAS") and primary, branched-chain and random C_{10} - C_{20} alkyl sulfates ("AS"), the C_{10} - C_{18} secondary (2,3) alkyl sulfates of the formula



where x and (y + 1) are integers of at least about 7, preferably at least about 9, and M is a water-solubilizing cation, especially sodium, unsaturated sulfates such as oleyl sulfate, the C₁₀-C₁₈ alkyl alkoxy sulfates ("AE₁S"); especially EO 1-7 ethoxy sulfates), C₁₀-C₁₈ alkyl alkoxy carboxylates (especially the EO 1-5 ethoxycarboxylates), the C₁₀-C₁₈ glycerol ethers, the C₁₀-C₁₈ alkyl polyglycosides and their corresponding sulfated polyglycosides, and C₁₂-C₁₈ alpha-sulfonated fatty acid esters. If desired, the conventional nonionic and amphoteric surfactants such as the C₁₂-C₁₈ alkyl ethoxylates ("AE") including the so-called narrow peaked alkyl ethoxylates and C₆-C₁₂ alkyl phenol alkoxy carboxylates (especially ethoxylates and mixed ethoxy/propoxy), C₁₂-C₁₈ betaines and sulfobetaines ("sultaines"), C₁₀-C₁₈ amine oxides, and the like, can also be included in the overall compositions. The C₁₀-C₁₈ N-alkyl polyhydroxy fatty acid amides can also be used. Typical examples include the C₁₂-C₁₈ N-methylglucamides. See WO 9,206,154. Other sugar-derived surfactants include the N-alkoxy polyhydroxy fatty acid amides, such as C₁₀-C₁₈ N-(3-methoxypropyl) glucamides. The N-propyl through N-hexyl C₁₂-C₁₈ glucamides can be used for low sudsing. C₁₀-C₂₀ conventional soaps may also be used. If high sudsing is desired, the branched-chain C₁₀-C₁₆ soaps may be used. Mixtures of anionic and nonionic surfactants are especially useful. Other conventional useful surfactants are listed in standard texts. In a preferred embodiment, the tablet comprises at least 5% per weight of surfactant, more preferably at least 15% per weight, even more preferably at least 25% per weight, and most preferably between 35% and 45% per weight of surfactant.

Non gelling binders

[0071] Non gelling binders can be integrated in detergent compositions to further facilitate dissolution.

If non gelling binders are used, suitable non-gelling binders include synthetic organic polymers such as polyethylene glycols, polyvinylpyrrolidones, polyacrylates and water-soluble acrylic copolymers. The handbook of Pharmaceutical Excipients second edition, has the following binders classification: Acacia, Alginate, Carbomer, Carboxymethylcellulose sodium, Dextrin, Ethylcellulose, Gelatin, Guar gum, Hydrogenated vegetable oil type I, Hydroxyethyl cellulose, Hydroxypropyl methylcellulose, Liquid glucose, Magnesium aluminum silicate, Maltodextrin, Methylcellulose, polymethacrylates, povidone, sodium alginate, starch and zein. Most preferable binders also have an active cleaning function in the laundry wash such as cationic polymers, i.e. ethoxylated hexamethylene diamine quaternary compounds, bishexamethylene triamines, or others such as pentaamines, ethoxylated polyethylene amines, maleic acrylic polymers.

Non-gelling binder materials are preferably sprayed on and hence have an appropriate melting point temperature below 90°C, preferably below 70°C and even more preferably below 50°C so as not to damage or degrade the other active ingredients in the matrix. Most preferred are non-aqueous liquid binders (i.e. not in aqueous solution) which may be sprayed in molten form. However, they may also be solid binders incorporated into the matrix by dry addition but which have binding properties within the tablet.

Non-gelling binder materials are preferably used in an amount within the range from 0.1 to 15% of the composition, more preferably below 5% and especially if it is a non laundry active material below 2% by weight of the tablet.

It is preferred that gelling binders, such as nonionic surfactants are avoided in their liquid or molten form. Nonionic surfactants and other gelling binders are not excluded from the compositions, but it is preferred that they be processed into the detergent tablets as components of particulate materials, and not as liquids.

Builders

[0072] Detergent builders can optionally be included in the compositions herein to assist in controlling mineral hardness. Inorganic as well as organic builders can be used. Builders are typically used in fabric laundering compositions to assist in the removal of particulate soils.

The level of builder can vary widely depending upon the end use of the composition.

Inorganic or P-containing detergent builders include, but are not limited to, the alkali metal, ammonium and alkano/ammonium salts of polyphosphates (exemplified by the triphosphates, pyrophosphates, and glassy polymeric metaphosphates), phosphonates, phytic acid, silicates, carbonates (including bicarbonates and sesquicarbonates), sulfates, and aluminosilicates. However, non-phosphate builders are required in some locales. Importantly, the compositions herein function surprisingly well even in the presence of the so-called "weak" builders (as compared with phosphates) such as citrate, or in the so-called "underbuilt" situation that may occur with zeolite or layered silicate builders.


Examples of silicate builders are the alkali metal silicates, particularly those having a SiO₂:Na₂O ratio in the range 1.6:1 to 3.2:1 and layered silicates, such as the layered sodium silicates described in U.S. Patent 4,664,839, issued May 12, 1987 to H. P. Rieck. NaSKS-6 is the trademark for a crystalline layered silicate marketed by Hoechst (commonly abbreviated herein as "SKS-6"). Unlike zeolite builders, the Na SKS-6 silicate builder does not contain aluminum.

NaSKS-6 has the delta- Na_2SiO_3 morphology form of layered silicate. It can be prepared by methods such as those described in German DE-A-3,417,649 and DE-A-3,742,043. SKS-6 is a highly preferred layered silicate for use herein, but other such layered silicates, such as those having the general formula $\text{NaMSi}_x\text{O}_{2x+1}\cdot y\text{H}_2\text{O}$ wherein M is sodium or hydrogen, x is a number from 1.9 to 4, preferably 2, and y is a number from 0 to 20, preferably 0 can be used herein.

Various other layered silicates from Hoechst include NaSKS-5, NaSKS-7 and NaSKS-11, as the alpha, beta and gamma forms. As noted above, the delta- Na_2SiO_3 (NaSKS-6 form) is most preferred for use herein. Other silicates may also be useful such as for example magnesium silicate, which can serve as a crispening agent in granular formulations, as a stabilizing agent for oxygen bleaches, and as a component of suds control systems.


Examples of carbonate builders are the alkaline earth and alkali metal carbonates as disclosed in German Patent Application No. 2,321,001 published on November 15, 1973.

Aluminosilicate builders are useful in the present invention. Aluminosilicate builders are of great importance in most currently marketed heavy duty granular detergent compositions, and can also be a significant builder ingredient in liquid detergent formulations. Aluminosilicate builders include those having the empirical formula:



wherein z and y are integers of at least 6, the molar ratio of z to y is in the range from 1.0 to about 0.5, and x is an integer from about 15 to about 264.

Useful aluminosilicate ion exchange materials are commercially available. These aluminosilicates can be crystalline or amorphous in structure and can be naturally-occurring aluminosilicates or synthetically derived. A method for producing aluminosilicate ion exchange materials is disclosed in U.S. Patent 3,985,669, Krummel, et al. issued October 12, 1976. Preferred synthetic crystalline aluminosilicate ion exchange materials useful herein are available under the designations Zeolite A, Zeolite P (B), Zeolite MAP and Zeolite X. In an especially preferred embodiment, the crystalline aluminosilicate ion exchange material has the formula:



wherein x is from about 20 to about 30, especially about 27. This material is known as Zeolite A. Dehydrated zeolites ($x = 0 - 10$) may also be used herein. Preferably, the aluminosilicate has a particle size of about 0.1-10 microns in diameter.

Organic detergent builders suitable for the purposes of the present invention include, but are not restricted to, a wide variety of polycarboxylate compounds. As used herein, "polycarboxylate" refers to compounds having a plurality of carboxylate groups, preferably at least 3 carboxylates. Polycarboxylate builder can generally be added to the composition in acid form, but can also be added in the form of a neutralized salt. When utilized in salt form, alkali metals, such as sodium, potassium, and lithium, or alkanolammonium salts are preferred.

Included among the polycarboxylate builders are a variety of categories of useful materials. One important category of polycarboxylate builders encompasses the ether polycarboxylates, including oxydisuccinate, as disclosed in Berg, U.S. Patent 3,128,287, issued April 7, 1964, and Lamberti et al. U.S. Patent 3,635,830, issued January 18, 1972. See also "TMS/TDS" builders of U.S. Patent 4,663,071, issued to Bush et al, on May 5, 1987.

Suitable ether polycarboxylates also include cyclic compounds, particularly alicyclic compounds, such as those described in U.S. Patents 3,923,679; 3,835,163; 4,158,635; 4,120,874 and 4,102,903.

Other useful detergency builders include the ether hydroxypolycarboxylates, copolymers of maleic anhydride with ethylene or vinyl methyl ether, 1, 3, 5-trihydroxy benzene-2, 4, 6-trisulphonic acid, and carboxymethyloxysuccinic acid, the various alkali metal, ammonium and substituted ammonium salts of polyacetic acids such as ethylenediamine tetraacetic acid and nitrilotriacetic acid, as well as polycarboxylates such as mellitic acid, succinic acid, oxy-disuccinic acid, polymaleic acid, benzene 1,3,5-tricarboxylic acid, carboxymethyloxysuccinic acid, and soluble salts thereof.

Citrate builders, e.g., citric acid and soluble salts thereof (particularly sodium salt), are polycarboxylate builders of particular importance for heavy duty liquid detergent formulations due to their availability from renewable resources and their biodegradability. Citrates can also be used in granular compositions, especially in combination with zeolite and/or layered silicate builders. Oxydisuccinates are also especially useful in such compositions and combinations. Also suitable in the detergent compositions of the present invention are the 3,3-dicarboxy-4-oxa-1,6-hexanedioates and the related compounds disclosed in U.S. Patent 4,566,984, Bush, issued January 28, 1986. Useful succinic acid builders include the $\text{C}_6\text{-C}_{20}$ alkyl and alkenyl succinic acids and salts thereof.

A particularly preferred compound of this type is dodecenylsuccinic acid. Specific examples of succinate builders include: laurylsuccinate, myristylsuccinate, palmitylsuccinate, 2-dodecenylsuccinate (preferred), 2-pentadecenylsuccinate, and the like. Laurylsuccinates are the preferred builders of this group, and are described in European Patent

Application 86200690 5/0,200,263, published November 5, 1986.

Other suitable polycarboxylates are disclosed in U.S. Patent 4,144,226, Crutchfield et al, issued March 13, 1979 and in U.S. Patent 3,308,067, Diehl, issued March 7, 1967. See also Diehl U.S. Patent 3,723,322.

Fatty acids, e.g., C₁₂-C₁₈ monocarboxylic acids, can also be incorporated into the compositions alone, or in combination with the aforesaid builders, especially citrate and/or the succinate builders, to provide additional builder activity. Such use of fatty acids will generally result in a diminution of sudsing, which should be taken into account by the formulator. In situations where phosphorus-based builders can be used, and especially in the formulation of bars used for hand-laundering operations, the various alkali metal phosphates such as the well-known sodium tripolyphosphates, sodium pyrophosphate and sodium orthophosphate can be used. Phosphonate builders such as ethane-1-hydroxy-1,1-diphosphonate and other known phosphonates (see, for example, U.S. Patents 3,159,581; 3,213,030; 3,422,021; 3,400,148 and 3,422,137) can also be used.

Bleach

[0073] The detergent compositions herein may optionally contain bleaching agents or bleaching compositions containing a bleaching agent and one or more bleach activators. When present, bleaching agents will typically be at levels of from about 1% to about 30%, more typically from about 5% to about 20%, of the detergent composition, especially for fabric laundering. If present, the amount of bleach activators will typically be from about 0.1% to about 60%, more typically from about 0.5% to about 40% of the bleaching composition comprising the bleaching agent-plus-bleach activator.

The bleaching agents used herein can be any of the bleaching agents useful for detergent compositions in textile cleaning, hard surface cleaning, or other cleaning purposes that are now known or become known. These include oxygen bleaches as well as other bleaching agents. Perborate bleaches, e.g., sodium perborate (e.g., mono- or tetrahydrate) can be used herein.

Another category of bleaching agent that can be used without restriction encompasses percarboxylic acid bleaching agents and salts thereof. Suitable examples of this class of agents include magnesium monoperoxyphthalate hexahydrate, the magnesium salt of metachloro perbenzoic acid, 4-nonylamino-4-oxoperoxybutyric acid and diperoxydecanedioic acid. Such bleaching agents are disclosed in U.S. Patent 4,483,781, Hartman, issued November 20, 1984, U.S. Patent Application 740,446, Burns et al, filed June 3, 1985, European Patent Application 0,133,354, Banks et al, published February 20, 1985, and U.S. Patent 4,412,934, Chung et al, issued November 1, 1983. Highly preferred bleaching agents also include 6-nonylamino-6-oxoperoxydecanoic acid as described in U.S. Patent 4,634,551, issued January 6, 1983 to Burns et al.


Peroxygen bleaching agents can also be used. Suitable peroxygen bleaching compounds include sodium carbonate peroxyhydrate and equivalent "percarbonate" bleaches, sodium pyrophosphate peroxyhydrate, urea peroxyhydrate, and sodium peroxide. Persulfate bleach (e.g., OXONE, manufactured commercially by DuPont) can also be used.

A preferred percarbonate bleach comprises dry particles having an average particle size in the range from about 500 micrometers to about 1,000 micrometers, not more than about 10% by weight of said particles being smaller than about 200 micrometers and not more than about 10% by weight of said particles being larger than about 1,250 micrometers. Optionally, the percarbonate can be coated with silicate, borate or water-soluble surfactants. Percarbonate is available from various commercial sources such as FMC, Solvay and Tokai Denka.

Mixtures of bleaching agents can also be used.

Peroxygen bleaching agents, the perborates, the percarbonates, etc., are preferably combined with bleach activators, which lead to the in situ production in aqueous solution (i.e., during the washing process) of the peroxy acid corresponding to the bleach activator. Various nonlimiting examples of activators are disclosed in U.S. Patent 4,915,854, issued April 10, 1990 to Mao et al, and U.S. Patent 4,412,934. The nonanoyloxybenzene sulfonate (NOBS) and tetraacetyl ethylene diamine (TAED) activators are typical, and mixtures thereof can also be used. See also U.S. 4,634,551 for other typical bleaches and activators useful herein.


Highly preferred amide-derived bleach activators are those of the formulae:




wherein R¹ is an alkyl group containing from about 6 to about 12 carbon atoms, R² is an alkylene containing from 1 to about 6 carbon atoms, R⁵ is H or alkyl, aryl, or alkaryl containing from about 1 to about 10 carbon atoms, and L is any suitable leaving group. A leaving group is any group that is displaced from the bleach activator as a consequence of the nucleophilic attack on the bleach activator by the perhydrolysis anion. A preferred leaving group is phenyl sulfonate. Preferred examples of bleach activators of the above formulae include (6-octanamido-caproyl)oxybenzenesulfonate, (6-nonanamidocaproyl)oxybenzene-sulfonate, (6-decanamido-caproyl)oxybenzenesulfonate, and mixtures thereof as

described in U.S. Patent 4,634,551, incorporated herein by reference.

Another class of bleach activators comprises the benzoxazin-type activators disclosed by Hodge et al in U.S. Patent 4,966,723, issued October 30, 1990, incorporated herein by reference. A highly preferred activator of the benzoxazin-type is:



Still another class of preferred bleach activators includes the acyl lactam activators, especially acyl caprolactams and acyl valerolactams of the formulae:



wherein R^6 is H or an alkyl, aryl, alkoxyaryl, or alkaryl group containing from 1 to about 12 carbon atoms. Highly preferred lactam activators include benzoyl caprolactam, octanoyl caprolactam, 3,5,5-trimethylhexanoyl caprolactam, nonanoyl caprolactam, decanoyl caprolactam, undecenoyl caprolactam, benzoyl valerolactam, octanoyl valerolactam, decanoyl valerolactam, undecenoyl valerolactam, nonanoyl valerolactam, 3,5,5-trimethylhexanoyl valerolactam and mixtures thereof. See also U.S. Patent 4,545,784, issued to Sanderson, October 8, 1985, incorporated herein by reference, which discloses acyl caprolactams, including benzoyl caprolactam, adsorbed into sodium perborate.

Bleaching agents other than oxygen bleaching agents are also known in the art and can be utilized herein. One type of non-oxygen bleaching agent of particular interest includes photoactivated bleaching agents such as the sulfonated zinc and/or aluminum phthalocyanines. See U.S. Patent 4,033,718, issued July 5, 1977 to Holcombe et al. If used, detergent compositions will typically contain from about 0.025% to about 1.25%, by weight, of such bleaches, especially sulfonated zinc phthalocyanine.

If desired, the bleaching compounds can be catalyzed by means of a manganese compound. Such compounds are well known in the art and include, for example, the manganese-based catalysts disclosed in U.S. Pat. 5,246,621, U.S. Pat. 5,244,594; U.S. Pat. 5,194,416; U.S. Pat. 5,114,606; and European Pat. App. Nos. 549,271A1, 549,272A1, 544,440A2, and 544,490A1; Preferred examples of these catalysts include $Mn^{IV}(u-O)_3(1,4,7\text{-trimethyl-1,4,7-triazacyclononane})_2(PF_6)_2$, $Mn^{III}(u-O)_3(u-OAc)_2(1,4,7\text{-trimethyl-1,4,7-triazacyclononane})_2(ClO_4)_2$, $Mn^{IV}(u-O)_6(1,4,7\text{-triazacyclononane})_2(ClO_4)_4$, $Mn^{III}Mn^{IV}_4(u-O)_3(u-OAc)_2(1,4,7\text{-trimethyl-1,4,7-triazacyclononane})_2(ClO_4)_2$, $Mn^{IV}(1,4,7\text{-trimethyl-1,4,7-triazacyclononane})-(OCH_3)_3(PF_6)_3$, and mixtures thereof. Other metal-based bleach catalysts include those disclosed in U.S. Pat. 4,430,243 and U.S. Pat. 5,114,611. The use of manganese with various complex ligands to enhance bleaching is also reported in the following United States Patents: 4,728,455; 5,284,944; 5,246,612; 5,256,779; 5,280,117; 5,274,147; 5,153,161; and 5,227,084.

As a practical matter, and not by way of limitation, the compositions and processes herein can be adjusted to provide on the order of at least one part per ten million of the active bleach catalyst species in the aqueous washing liquor, and will preferably provide from about 0.1 ppm to about 700 ppm, more preferably from about 1 ppm to about 500 ppm, of the catalyst species in the laundry liquor.

Enzymes

[0074] Enzymes can be included in the formulations herein for a wide variety of fabric laundering purposes, including removal of protein-based, carbohydrate-based, or triglyceride-based stains, for example, and for the prevention of refugee dye transfer, and for fabric restoration. The enzymes to be incorporated include proteases, amylases, lipases, cellulases, and peroxidases, as well as mixtures thereof. Other types of enzymes may also be included. They may be of any suitable origin, such as vegetable, animal, bacterial, fungal and yeast origin.

However, their choice is governed by several factors such as pH-activity and/or stability optima, thermostability, stability

versus active detergents, builders and so on. In this respect bacterial or fungal enzymes are preferred, such as bacterial amylases and proteases, and fungal cellulases.

Enzymes are normally incorporated at levels sufficient to provide up to about 5 mg by weight, more typically about 0.01 mg to about 3 mg, of active enzyme per gram of the composition. Stated otherwise, the compositions herein will typically comprise from about 0.001% to about 5%, preferably 0.01%-1% by weight of a commercial enzyme preparation. Protease enzymes are usually present in such commercial preparations at levels sufficient to provide from 0.005 to 0.1 Anson units (AU) of activity per gram of composition.

Suitable examples of proteases are the subtilisins which are obtained from particular strains of *B. subtilis* and *B. licheniformis*. Another suitable protease is obtained from a strain of *Bacillus*, having maximum activity throughout the pH range of 8-12, developed and sold by Novo Industries A/S under the registered trade name ESPERASE. The preparation of this enzyme and analogous enzymes is described in British Patent Specification No. 1,243,784 of Novo. Proteolytic enzymes suitable for removing protein-based stains that are commercially available include those sold under the tradenames ALCALASE and SAVINASE by Novo Industries A/S (Denmark) and MAXATASE by International Bio-Synthetics, Inc. (The Netherlands). Other proteases include Protease A (see European Patent Application 130,756, published January 9, 1985) and Protease B (see European Patent Application Serial No. 87303761.8, filed April 28, 1987, and European Patent Application 130,756, Bott et al., published January 9, 1985).

Amylases include, for example, α -amylases described in British Patent Specification No. 1,296,839 (Novo), RAPI-DASE, International Bio-Synthetics, Inc. and TERMAMYL, Novo Industries.

The cellulase usable in the present invention include both bacterial or fungal cellulase. Preferably, they will have a pH optimum of between 5 and 9.5. Suitable cellulases are disclosed in U.S. Patent 4,435,307, Barbesgoard et al., issued March 6, 1984, which discloses fungal cellulase produced from *Humicola insolens* and *Humicola* strain DSM1800 or a cellulase 212-producing fungus belonging to the genus *Aeromonas*, and cellulase extracted from the hepatopancreas of a marine mollusk (*Dolabella Auricula Solanderi*). Suitable cellulases are also disclosed in GB-A-2,075,028; GB-A-2,095,275 and DE-OS-2,247,832. CAREZYME (Novo) is especially useful.

Suitable lipase enzymes for detergent usage include those produced by microorganisms of the *Pseudomonas* group, such as *Pseudomonas stutzeri* ATCC 19,154, as disclosed in British Patent 1,372,034. See also lipases in Japanese Patent Application 53,20487, laid open to public inspection on February 24, 1978. This lipase is available from Amano Pharmaceutical Co. Ltd., Nagoya, Japan, under the trade name Lipase P "Amano," hereinafter referred to as "Amano-P." Other commercial lipases include Amano-CES, lipases ex *Chromobacter viscosum*, e.g. *Chromobacter viscosum* var. *lipolyticum* NRRLB 3673, commercially available from Toyo Jozo Co., Tagata, Japan; and further *Chromobacter viscosum* lipases from U.S. Biochemical Corp., U.S.A. and Disocynth Co., The Netherlands; and lipases ex *Pseudomonas gladioli*. The LIPOLEASE enzyme derived from *Humicola lanuginosa* and commercially available from Novo (see also EPO 341,947) is a preferred lipase for use herein.

Peroxidase enzymes are used in combination with oxygen sources, e.g., percarbonate, perborate, persulfate, hydrogen peroxide, etc. They are used for "solution bleaching," i.e. to prevent transfer of dyes or pigments removed from substrates curing wash operations to other substrates in the wash solution. Peroxidase enzymes are known in the art, and include, for example, horseradish peroxidase, ligninase, and haloperoxidase such as chloro- and bromo-peroxidase. Peroxidase-containing detergent compositions are disclosed, for example, in PCT International Application WO 89/099813, published October 19, 1989, by O. Kirk, assigned to Novo Industries A/S.

A wide range of enzyme materials and means for their incorporation into synthetic detergent compositions are also disclosed in U.S. Patent 3,553,139, issued January 5, 1971 to McCarty et al. Enzymes are further disclosed in U.S. Patent 4,101,457, Place et al., issued July 18, 1978, and in U.S. Patent 4,507,219, Hughes, issued March 26, 1985, both. Enzyme materials useful for liquid detergent formulations, and their incorporation into such formulations, are disclosed in U.S. Patent 4,261,868, Hora et al., issued April 14, 1981. Enzymes for use in detergents can be stabilized by various techniques. Enzyme stabilization techniques are disclosed and exemplified in U.S. Patent 3,600,319, issued August 17, 1971 to Gedde, et al. and European Patent Application Publication No. 0 199 405, Application No. 86200586.5, published October 29, 1986, Venegas. Enzyme stabilization systems are also described, for example, in U.S. Patent 3,519,570.

Flocculating agent

[0075] The detergent composition may contain a clay flocculating agent, preferably present at a level of from 0.005% to 10%, more preferably from 0.05% to 5%, most preferably from 0.1% to 2% by weight of the composition.

[0076] The clay flocculating agent functions such as to bring together the particles of clay compound in the wash solution and hence to aid their deposition onto the surface of the fabrics in the wash. This functional requirement is hence different from that of clay dispersant compounds which are commonly added to laundry detergent compositions to aid the removal of clay soils from fabrics and enable their dispersion within the wash solution.

[0077] Preferred as clay flocculating agents herein are organic polymeric materials having an average weight of from

100,000 to 10,000,000, preferably from 150,000 to 5,000,000, more preferably from 200,000 to 2,000,000.

[0078] Suitable organic polymeric materials comprise homopolymers or copolymers containing monomeric units selected from alkylene oxide, particularly ethylene oxide, acrylamide, acrylic acid, vinyl alcohol, vinyl pyrrolidone, and ethylene imine. Homopolymers of, on particular, ethylene oxide, but also acrylamide and acrylic acid are preferred.

[0079] European Patents No.s EP-A-299,575 and EP-A-313,146 in the name of the Procter and Gamble Company describe preferred organic polymeric clay flocculating agents for use herein.

[0080] Inorganic clay flocculating agents are also suitable herein, typical examples of which include lime and alum.

[0081] The flocculating agent is preferably present in a detergent base granule such as a detergent agglomerate, extrudate or spray-dried particle, comprising generally one or more surfactants and builders.

[0082] It may be preferred that the flocculating agent is also comprised in the particles or granule comprising the clay.

[0083] When present, the weight ratio of clay to the flocculating polymer is preferably from 1000:1 to 1:1, more preferably from 500:1 to 1:1, most preferably from 300:1 to 1:1, or even more preferably from 80:1 to 10:1, or in certain applications even from 60:1 to 20:1.

Highly soluble Compounds

[0084] The tablet may comprise a highly soluble compound. Such a compound could be formed from a mixture or from a single compound. A highly soluble compound is defined as follow:

A solution is prepared as follows comprising de-ionised water as well as 20 grams per litre of a specific compound:

1- 20 g of the specific compound is placed in a Sotax Beaker. This beaker is placed in a constant temperature bath set at 10°C. A stirrer with a marine propeller is placed in the beaker so that the bottom of the stirrer is at 5 mm above the bottom of the Sotax beaker. The mixer is set at a rotation speed of 200 turns per minute.

2- 980 g of the de-ionised water is introduced into the Sotax beaker.

3- 10 s after the water introduction, the conductivity of the solution is measured, using a conductivity meter.

4- Step 3 is repeated after 20, 30, 40, 50, 1 min, 2 min, 5 min and 10 min after step 2.

5- The measurement taken at 10 min is used as the plateau value or maximum value.

[0085] The specific compound is highly soluble according to the invention when the conductivity of the solution reaches 80% of its maximum value in less than 10 seconds, starting from the complete addition of the de-ionised water to the compound. Indeed, when monitoring the conductivity in such a manner, the conductivity reaches a plateau after a certain period of time, this plateau being considered as the maximum value. Such a compound is preferably in the form of a flowable material constituted of solid particles at temperatures comprised between 10 and 80°Celsius for ease of handling, but other forms may be used such as a paste or a liquid.

Example of highly soluble compounds include Sodium di isoalkylbenzene sulphonate (DIBS) or Sodium toluene sulphonate.

Cohesive Effect

[0086] The tablet may comprise a compound having a Cohesive Effect on the particulate material of a detergent matrix forming the tablet. The Cohesive Effect on the particulate material of a detergent matrix forming the tablet or a layer of the tablet is characterised by the force required to break a tablet or layer based on the examined detergent matrix pressed under controlled compression conditions. For a given compression force, a high tablet or layer strength indicates that the granules stuck highly together when they were compressed, so that a strong cohesive effect is taking place. Means to assess tablet or layer strength (also refer to diametrical fracture stress) are given in Pharmaceutical dosage forms : tablets volume 1 Ed. H.A. Lieberman et al, published in 1989.

[0087] The cohesive effect is measured by comparing the tablet or layer strength of the original base powder without compound having a cohesive effect with the tablet or layer strength of a powder mix which comprises 97 parts of the original base powder and 3 parts of the compound having a cohesive effect. The compound having a cohesive effect is preferably added to the matrix in a form in which it is substantially free of water (water content below 10% (pref. below 5%)). The temperature of the addition is between 10 and 80°C, more pref. between 10 and 40°C.

A compound is defined as having a cohesive effect on the particulate material according to the invention when at a given compacting force of 3000N, tablets with a weight of 50g of detergent particulate material and a diameter of 55mm have their tablet tensile strength increased by over 30% (preferably 60 and more preferably 100%) by means of the presence of 3% of the compound having a cohesive effect in the base particulate material.

An example of a compound having a cohesive effect is Sodium di isoalkylbenzene sulphonate.

[0088] When integrating a highly soluble compound having also a cohesive effect on the particulate material used for a tablet or layer formed by compressing a particulate material comprising a surfactant, the dissolution of the tablet

or layer in an aqueous solution is significantly increased.

[0089] In a preferred embodiment, at least 1 % per weight of a tablet or layer is formed from the highly soluble compound, more preferably at least 2%, even more preferably at least 3% and most preferably at least 5% per weight of the tablet or layer being formed from the highly soluble compound having a cohesive effect on the particulate material.

[0090] It should be noted that a composition comprising a highly soluble compound as well as a surfactant is disclosed in EP-A-0 524 075, this composition being a liquid composition.

[0091] A highly soluble compound having a cohesive effect on the particulate material allows to obtain a tablet having a higher tensile strength at constant compacting force or an equal tensile strength at lower compacting force when compared to traditional tablets. Typically, a whole tablet will have a tensile strength of more than 5kPa, preferably of more than 10kPa, more preferably, in particular for use in laundry applications, of more than 15kPa, even more preferably of more than 30 kPa and most preferably of more than 50 kPa, in particular for use in dish washing or auto dish washing applications; and a tensile strength of less than 300 kPa, preferably of less than 200 kPa, more preferably of less than 100 kPa, even more preferably of less than 80 kPa and most preferably of less than 60 kPa. Indeed, in case of laundry application, the tablets should be less compressed than in case of auto dish washing applications for example, whereby the dissolution is more readily achieved, so that in a laundry application, the tensile strength is preferably of less than 30 kPa.

[0092] This allows to produce tablets or layers which have a solidity and mechanical resistance comparable to the solidity or mechanical resistance of traditional tablets while having a less compact tablet or layer thus dissolving more readily. Furthermore, as the compound is highly soluble, the dissolution of the tablet or layer is further facilitated, resulting in a synergy leading to facilitated dissolution for a tablet according to the invention.

Tablet Manufacture

[0093] The tablet may comprise several layers. For the purpose of manufacture of a single layer, the layer may be considered as a tablet itself.

Detergent tablets can be prepared simply by mixing the solid ingredients together and compressing the mixture in a conventional tablet press as used, for example, in the pharmaceutical industry. Preferably the principal ingredients, in particular gelling surfactants, are used in particulate form. Any liquid ingredients, for example surfactant or suds suppressor, can be incorporated in a conventional manner into the solid particulate ingredients.

[0094] In particular for laundry tablets, the ingredients such as builder and surfactant can be spray-dried in a conventional manner and then compacted at a suitable pressure. Preferably, the tablets according to the invention are compressed using a force of less than 100000N, more preferably of less than 50000N, even more preferably of less than 5000N and most preferably of less than 3000 N. Indeed, the most preferred embodiment is a tablet suitable for laundry compressed using a force of less than 2500N, but tablets for auto dish washing may also be considered for example, whereby such auto dish washing tablets are usually more compressed than laundry tablets.

[0095] The particulate material used for making a tablet can be made by any particulation or granulation process. An example of such a process is spray drying (in a co-current or counter current spray drying tower) which typically gives low bulk densities 600g/l or lower. Particulate materials of higher density can be prepared by granulation and densification in a high shear batch mixer/granulator or by a continuous granulation and densification process (e.g. using Lodge® CB and/or Lodge® KM mixers). Other suitable processes include fluid bed processes, compaction processes (e.g. roll compaction), extrusion, as well as any particulate material made by any chemical process like flocculation, crystallisation sintering, etc. Individual particles can also be any other particle, granule, sphere or grain.

[0096] The components of the particulate material may be mixed together by any conventional means. Batch is suitable in, for example, a concrete mixer, Nauta mixer, ribbon mixer or any other. Alternatively the mixing process may be carried out continuously by metering each component by weight on to a moving belt, and blending them in one or more drum(s) or mixer(s). Non-gelling binder can be sprayed on to the mix of some, or all of, the components of the particulate material. Other liquid ingredients may also be sprayed on to the mix of components either separately or premixed. For example perfume and slurries of optical brighteners may be sprayed. A finely divided flow aid (dusting agent such as zeolites, carbonates, silicas) can be added to the particulate material after spraying the binder, preferably towards the end of the process, to make the mix less sticky.

[0097] The tablets may be manufactured by using any compacting process, such as tableting, briquetting, or extrusion, preferably tableting. Suitable equipment includes a standard single stroke or a rotary press (such as Courtoy®, Korch®, Manesty®, or Bonaldi®). The tablets prepared according to this invention preferably have a diameter of between 20mm and 60mm, preferably of at least 35 and up to 55 mm, and a weight between 25 and 100 g. The ratio of height to diameter (or width) of the tablets is preferably greater than 1:3, more preferably greater than 1:2. The compaction pressure used for preparing these tablets need not exceed 100000 kN/m², preferably not exceed 30000 kN/m², more preferably not exceed 5000 kN/m², even more preferably not exceed 3000kN/m² and most preferably not exceed 1000kN/m². In a preferred embodiment according to the invention, the tablet has a density of at least 0.9 g/cc.

more preferably of at least 1.0 g/cc, and preferably of less than 2.0 g/cc, more preferably of less than 1.5 g/cc, even more preferably of less than 1.25 g/cc and most preferably of less than 1.1 g/cc.

[0098] Multi layered tablets are typically formed in rotating presses by placing the matrices of each layer, one after the other in matrix force feeding flasks. As the process continues, the matrix layers are then pressed together in the precompression and compression stages stations to form the multilayer layer tablet. With some rotating presses it is also possible to compress the first feed layer before compressing the whole tablet.

Hydrotrope compound

[0099] A highly soluble compound having a cohesive effect may be integrated to a detergent tablet, whereby this compound is also a hydrotrope compound. Such hydrotrope compound may be generally used to favour surfactant dissolution by avoiding gelling. A specific compound is defined as being hydrotrope as follows (see S.E. Friberg and M. Chiu, J. Dispersion Science and Technology, 9(5&6), pages 443 to 457, (1988-1989)):

1. A solution is prepared comprising 25% by weight of the specific compound and 75% by weight of water.
2. Octanoic Acid is thereafter added to the solution in a proportion of 1.6 times the weight of the specific compound in solution, the solution being at a temperature of 20° Celsius. The solution is mixed in a Sotax beaker with a stirrer with a marine propeller, the propeller being situated at about 5mm above the bottom of the beaker, the mixer being set at a rotation speed of 200 rounds per minute.
3. The specific compound is hydrotrope if the the Octanoic Acid is completely solubilised, i.e. if the solution comprises only one phase, the phase being a liquid phase.

It should be noted that in a preferred embodiment of the invention, the hydrotrope compound is a flowable material made of solid particles at operating conditions between 15 and 60° Celsius.


Hydrotrope compounds include the compounds listed thereafter:

[0100] A list of commercial hydrotropes can be found in McCutcheon's Emulsifiers and Detergents published by the McCutcheon division of Manufacturing Confectioners Company.

Compounds of interest also include:

[0101]

1. Nonionic hydrotrope with the following structure:




where R is a C8-C10 alkyl chain, x ranges from 1 to 15, y from 3 to 10.

2. Anionic hydrotropes such as alkali metal aryl sulfonates. This includes alkali metal salts of benzoic acid, salicylic acid, benzenesulfonic acid and its many derivatives, naphthoic acid and various hydroaromatic acids. Examples of these are sodium, potassium and ammonium benzene sulfonate salts derived from toluene sulfonic acid, xylene sulfonic acid, cumene sulfonic acid, tetralin sulfonic acid, naphthalene sulfonic acid, methyl- naphthalene sulfonic acid, dimethyl naphthalene sulfonic acid, trimethyl naphthalene sulfonic acid=

Other examples include salts of dialkyl benzene sulfonic acid such as salts of di-isopropyl benzene sulfonic acid, ethyl methyl benzene sulfonic acid, alkyl benzene sulfonic acid with an alkyl chain length with 3 to 10, (pref. 4 to 9), linear or branched alkyl sulfonates with an alkyl chain with 1 to 18 carbons.

3. Solvent hydrotropes such as alkoxylated glycerines and alkoxylated glycerides, esters alkoxylated glycerines, alkoxylated fatty acids, esters of glycerin, polyglycerol esters. Preferred alkoxylated glycerines have the following structure:



where l, m and n are each a number from 0 to about 20, with l+m+n = from about 2 to about 60, preferably from about 10 to about 45 and R represents H, CH₃ or C₂H₅

Preferred alkoxylated glycerides have the following structure



where R₁ and R₂ are each C_nCOO or -(CH₂CHR₃-O)-H where R₃ = H, CH₃ or C₂H₅ and l is a number from 1 to about 60, n is a number from about 6 to about 24.

4. Polymeric hydrotropes such as those described in EP636687:



where E is a hydrophilic functional group,

R is H or a C1-C10 alkyl group or is a hydrophilic functional group;

R₁ is H or a lower alkyl group or an aromatic group,

R₂ is H or a cyclic alkyl or aromatic group.

The polymer typically has a molecular weight of between about 1000 and 1000000.

5. Hydrotrope of unusual structure such as 5-carboxy-4-hexyl-2-cyclohexene-1-yl octanoic acid (Diacid®)

Use of such compound in the invention would further increase the dissolution rate of the tablet, as a hydrotrope compound facilitates dissolution of surfactants, for example. Such a compound could be formed from a mixture or from a single compound.

Tensile Strength

[0102] For the purpose of measuring tensile strength of a layer, the layer may be considered as a tablet itself.

Depending on the composition of the starting material, and the shape of the tablets, the used compacting force may be adjusted to not affect the tensile strength, and the disintegration time in the washing machine. This process may be used to prepare homogenous or layered tablets of any size or shape. For a cylindrical tablet, the tensile strength corresponds to the diametrical fracture stress (DFS) which is a way to express the strength of a tablet or layer, and is determined by the following equation:

$$\text{Tensile strength} = 2 F / \pi D t$$

Where F is the maximum force (Newton) to cause tensile failure (fracture) measured by a VK 200 tablet hardness tester supplied by Van Kell Industries, Inc. D is the diameter of the tablet or layer, and t the thickness of the tablet or

layer. For a non round tablet, πd may simply be replaced by the perimeter of the tablet.

(Method Pharmaceutical Dosage Forms : Tablets Volume 2 Page 213 to 217).

A tablet having a diametral fracture stress of less than 20 kPa is considered to be fragile and is likely to result in some broken tablets being delivered to the consumer. A diametral fracture stress of at least 25 kPa is preferred.

This applies similarly to non cylindrical tablets, to define the tensile strength, whereby the cross section normal to the height of the tablet is not round, and whereby the force is applied along a direction perpendicular to the direction of the height of the tablet and normal to the side of the tablet, the side being perpendicular to the non round cross section.

Tablet Dispensing

[0103] The rate of dispensing of a detergent tablet can be determined in the following way:

Two tablets, nominally 50 grams each, are weighed, and then placed in the dispenser of a Baucknecht® WA9850 washing machine. The water supply to the washing machine is set to a temperature of 20 °C and a hardness of 21 grains per gallon, the dispenser water inlet flow-rate being set to 8 l/min. The level of tablet residues left in the dispenser is checked by switching the washing on and the wash cycle set to wash program 4 (white/colors, short cycle). The dispensing percentage residue is determined as follows:

$$\% \text{ dispensing} = \text{residue weight} \times 100 / \text{original tablet weight}$$

The level of residues is determined by repeating the procedure 10 times and an average residue level is calculated based on the ten individual measurements. In this stressed test a residue of 40 % of the starting tablet weight is considered to be acceptable. A residue of less than 30% is preferred, and less than 25% is more preferred.

It should be noted that the measure of water hardness is given in the traditional "grain per gallon" unit, whereby 0.001 mole per litre = 7.0 grain per gallon, representing the concentration of Ca^{2+} ions in solution.

Effervescent

[0104] Detergent tablets may further comprise an effervescent.

Effervescency as defined herein means the evolution of bubbles of gas from a liquid, as the result of a chemical reaction between a soluble acid source and an alkali metal carbonate, to produce carbon dioxide gas,



Further examples of acid and carbonate sources and other effervescent systems may be found in : (Pharmaceutical Dosage Forms : Tablets Volume 1 Page 287 to 291).

An effervescent may be added to the tablet mix in addition to the detergent ingredients. The addition of this effervescent to the detergent tablet improves the disintegration time of the tablet. The amount will preferably be between 5 and 20 % and most preferably between 10 and 20% by weight of the tablet. Preferably the effervescent should be added as an agglomerate of the different particles or as a compact, and not as separated particles.

Due to the gas created by the effervescency in the tablet, the tablet can have a higher D.F.S. and still have the same disintegration time as a tablet without effervescency. When the D.F.S. of the tablet with effervescency is kept the same as a tablet without, the disintegration of the tablet with effervescency will be faster.

Further dissolution aid could be provided by using compounds such as sodium acetate or urea. A list of suitable dissolution aid may also be found in Pharmaceutical Dosage Forms: Tablets, Volume 1, Second edition, Edited by H.A. Lieberman et al., ISBN 0-8247-8044-2.

Other components which are commonly used in detergent compositions and which may be incorporated into detergent tablets include chelating agents, soil release agents, soil antiredeposition agents, dispersing agents, suds suppressors, fabric softeners, dye transfer inhibition agents and mixtures thereof.

Coating

[0105] Solidity of a tablet may be improved by making a coated tablet, the coating covering a non-coated tablet, thereby further improving the mechanical characteristics of the tablet while maintaining or further improving dissolution.

[0106] This very advantageously applies to multi-layer tablets, whereby the mechanical characteristics of a more elastic layer can be transmitted via the coating to the rest of the tablet, thus combining the advantage of the coating with the advantage of the more elastic layer. Indeed, mechanical constraints will be transmitted through the coating,

thus improving mechanical integrity of the tablet.

[0107] In one embodiment of the present invention, the tablets may then be coated so that the tablet does not absorb moisture, or absorbs moisture at only a very slow rate. The coating is also strong so that moderate mechanical shocks to which the tablets are subjected during handling, packing and shipping result in no more than very low levels of breakage or attrition. Finally the coating is preferably brittle so that the tablet breaks up quickly when subjected to stronger mechanical shock. Furthermore it is advantageous if the coating material is dissolved under alkaline conditions, or is readily emulsified by surfactants. This contributes to avoiding the problem of visible residue in the window of a front-loading washing machine during the wash cycle, and also avoids deposition of undissolved particles or lumps of coating material on the laundry load.

[0108] Water solubility is measured following the test protocol of ASTM E1148-87 entitled, "Standard Test Method for Measurements of Aqueous Solubility".

[0109] Fracture of the coating in the wash is improved by adding a disintegrant in the coating. This disintegrant will swell once in contact with water and break the coating in small pieces. This will improve the dissolution of the coating in the wash solution. Typically, the disintegrant is suspended in the coating melt at a level of up to 30%, preferably between 5% and 20%, most preferably between 5 and 10% by weight.

[0110] Clay mineral compound, as above described, is a disintegrant for use herein.

[0111] Other possible disintegrants which may be used in addition to the clay disintegrants are described in Handbook of Pharmaceutical Excipients (1986). Examples of suitable disintegrants include starch: natural, modified or pregelatinized starch, sodium starch gluconate; gum: agar gum, guar gum, locust bean gum, karaya gum, pectin gum, tragacanth gum; croscarmellose Sodium, crospovidone, cellulose, carboxymethyl cellulose, alginic acid and its salts including sodium alginate, silicone dioxide, clay, polyvinylpyrrolidone, soy polysaccharides, ion exchange resins, polymers containing cationic (e.g. quaternary ammonium) groups, amine-substituted polyacrylates, polymerised cationic amino acids such as poly-L-lysine, polyallylamine hydrochloride) and mixtures thereof.

[0112] Preferably, the coating material has a melting point of at least 40°C, preferably of 40°C to 260 °C.

[0113] By "melting point" is meant the temperature at which the material when heated slowly in, for example, a capillary tube becomes a clear liquid.

[0114] Preferably, the coating material which has a melting point of at least 40°C is an acid. Acid having a melting temperature of at least 40°C are for example dicarboxylic acids. Particularly suitable dicarboxylic acids are selected from the group consisting of oxalic acid, malonic acid, succinic acid, glutaric acid, adipic acid, pimelic acid, suberic acid, azelaic acid, sebacic acid, undecanedioic acid, dodecanedioic acid, tridecanedioic acid and mixtures thereof. Most preferred is adipic acid.

[0115] More preferably, the coating comprises a crystallised structure. By crystallised, it should be understood that the coating comprises a material which is solid at ambient temperature (25°C) and has a structure exhibiting some order. This can be detected typically by usual crystallography techniques e.g. X-ray analysis, on the material itself. In a more preferred embodiment, the material forming the crystallised structure does not co-crystallise or only partially with the optional component which is liquid at 25°C mentioned above. Indeed, it is preferred that the optional component remains in the liquid state at 25°C in the coating crystalline structure in order to provide flexibility to the structure and resistance to mechanical stress. Most preferably, the above mentioned acid having a melting temperature of at least 40°C comprises a crystallised structure.

[0116] Clearly substantially insoluble materials having a melting point below 40 °C are not sufficiently solid at ambient temperatures and it has been found that materials having a melting point above about 200 °C are not practicable to use. Preferably, an acid having a melting point of more than 90°C such as azelaic, sebacic acid, dodecanedioic acid. However, for the purpose of the present invention, the use of sebacic acid is less preferred as it provides a detrimental odour to the resulting product. According to the invention, it was found that an acid having a melting point of more than 145°C such as adipic was found particularly suitable.

[0117] The coating can be applied in a number of ways. Two preferred coating methods are a) coating with a molten material and b) coating with a solution of the material.

In a), the coating material is applied at a temperature above its melting point, and solidifies on the tablet. In b), the coating is applied as a solution, the solvent being dried to leave a coherent coating. The substantially insoluble material can be applied to the tablet by, for example, spraying or dipping. Normally when the molten material is sprayed on to the tablet, it will rapidly solidify to form a coherent coating. When tablets are dipped into the molten material and then removed, the rapid cooling again causes rapid solidification of the coating material. During the solidification phase, the coating undergoes some internal stress (e.g. shrinkage upon cooling) and external stress (e.g. tablet relaxation). This will likely cause some cracks in the structure such as edge splitting if the coating material is too brittle to withstand these mechanical stress, which is the case when a coating is solely made from components solid at 25°C. Thus, it is preferred that the coating comprises a component which is liquid at 25°C. Hence, it is believed that this liquid component will allow the coating to better withstand and absorb mechanical stress by rendering the coating structure more flexible. The component which is liquid at 25°C is preferably added to the coating materials in proportions of less than 10% by

weight of the coating, more preferably less than 5% by weight, and most preferably of less than 3% by weight. The component which is liquid at 25°C is preferably added to the coating materials in proportions of more than 0.1% by weight of the coating, more preferably more than 0.3% by weight, and most preferably of more than 0.5% by weight.

[0118] Examples of optional components which are liquid at 25°C includes polyethylene glycols, thermal oil, silicon oil, esters of dicarboxylic acids, mono carboxylic acids, paraffin, triacetin, perfumes or alkaline solutions. For example, particularly good results were obtained by use of NaOH solution as alkaline solution.

[0119] It is preferred that the structure of the components which is liquid at 25°C is close to the material forming the crystallised structure, so that the structure is not excessively disrupted.

[0120] In another embodiment, the optional component which is liquid at 25°C may advantageously have a functionality in the washing of laundry, for example silicone oil which provides suds suppression benefits or perfume oil. When present, the perfume oil may be the perfume composition as per described herein, or a different perfume composition to that already contained by the tablet, provided it contains less than 0.6% by weight of Schiff-Base.

[0121] The coating may also comprise materials other than the optional component which is liquid at 25°C. Hence, further preferred, is the addition of reinforcing fibres to the coating in order to further reinforce the structure.

[0122] In a most preferred embodiment, the crystallised structure is made of adipic acid, the component which is liquid at 25°C being available under the name Coasol™ from Chemoxy International, being a blend of the di-isobutyl esters of the glutaric, succinic and adipic acid. The advantage of the use of this component being the good dispersion in the adipic acid to provide flexibility. It should be noted that disintegration of the adipic acid is further improved by the adipate content of Coasol™.

[0123] According to a preferred embodiment of the invention, the coating comprises an acid having a melting temperature of at least 145°C, such as adipic acid for example, as well as a clay, such as a bentonite clay for example, whereby the clay is used as a disintegrant and also to render the structure of adipic acid more favourable for water penetration, thus improving the dispersion of the adipic acid in an aqueous medium. Preferred are clays having a particle size of less than 75 µm, more preferably of less than 53 µm, in order to obtain the desired effect on the structure of the acid. Preferred clays are bentonite clays. Indeed the acid has a melting point such that traditional cellulosic disintegrants undergo a thermal degradation during the coating process, whereas such clays are found to be more heat stable. Further, traditional cellulosic disintegrant such as Nymcel™ for example are found to turn brown at these temperatures.

[0124] In another preferred embodiment, the coating further comprises reinforcing fibres. Such fibres have been found to improve further the resistance of the coating to mechanical stress and minimise the splitting defect occurrence. Such fibres are preferably having a length of at least 100 µm, more preferably of at least 200 µm and most preferably of at least 250 µm to allow structure reinforcement. Such fibres are preferably having a length of at least 500 µm, more preferably of less than 400 µm and most preferably of less than 350 µm in order not to impact onto dispersion of the coating in an aqueous medium. Materials which may be used for these fibres include viscose rayon, natural nylon, synthetic nylon (polyamides types 6 and 6,6), acrylic, polyester, cotton and derivatives of cellulose such as CMCs. Most preferred is a cellulosic material available under the trade mark Solka-Floc™ from Fibers Sales & Development. It should be noted that such fibres do not normally need precompression for reinforcing the coating structure. Such fibres are preferably added at a level of less than 5% by weight of the coating, more preferably less than 3% by weight. Such fibres are preferably added at a level of more than 0.5% by weight of the coating, more preferably more than 1% by weight.

[0125] A coating of any desired thickness can be applied according to the present invention. For most purposes, the coating forms from 1% to 10%, preferably from 1.5% to 5%, of the tablet weight.

[0126] Tablet coatings are very hard and provide extra strength to the tablet.

Process

[0127] A preferred process for making a tablet according to the invention comprises the steps of:

- (a) forming a core by compressing a particulate material, the particulate material comprising surfactant and detergent builder;
- (b) applying a coating material to the core, the coating material being in the form of a melt;
- (c) allowing the molten coating material to solidify;

characterised in that the coating comprises a clay.

[0128] Another preferred process for making a tablet according to the invention comprises the steps of:

- (a) forming a core by compressing a particulate material, the particulate material comprising surfactant and detergent builder;

- (b) applying a coating material to the core, the coating material being dissolved in a solvent or water;
 (c) allowing the solvent or water to evaporate;

characterised in that the coating comprises a clay.

[0129] The compounds disclosed above for a product are advantageously packed in a packaging system.

A packaging system may be formed from a sheet of flexible material. Materials suitable for use as a flexible sheet include mono-layer, co-extruded or laminated films. Such films may comprise various components, such as poly-ethylene, poly-propylene, poly-styrene, poly-ethylene-terephthalate. Preferably, the packaging system is composed of a poly-ethylene and bi-oriented-poly-propylene co-extruded film with an MVTR of less than 5 g/day/m². The MVTR of the packaging system is preferably of less than 10 g/day/m², more preferably of less than 5 g/day/m². The film (2) may have various thicknesses. The thickness should typically be between 10 and 150 µm, preferably between 15 and 120 µm, more preferably between 20 and 100 µm, even more preferably between 25 and 80 µm and most preferably between 30 and 40 µm.

A packaging material preferably comprises a barrier layer typically found with packaging materials having a low oxygen transmission rate, typically of less than 300 cm³/m²/day, preferably of less than 150 cm³/m²/day, more preferably of less than 100 cm³/m²/day, even more preferably of less than 50 cm³/m²/day and most preferably of less than 10 cm³/m²/day. Typical materials having such barrier properties include bi oriented polypropylene, poly ethylene terephthalate, Nylon, poly(ethylene vinyl alcohol), or laminated materials comprising one of these, as well as SiOx (Silicium oxides), or metallic foils such as aluminium foils for example. Such packaging material may have a beneficial influence on the stability of the product during storage for example. Among the packing method used are typically the wrapping methods disclosed in WO92/20593, including flow wrapping or over wrapping. When using such processes, a longitudinal seal is provided, which may be a fin seal or an overlapping seal, after which a first end of the packaging system is closed with a first end seal, followed by closure of the second end with a second end seal. The packaging system may comprise re-closing means as described in WO92/20593. In particular, using a twist, a cold seal or an adhesive is particularly suited. Indeed, a band of cold seal or a band of adhesive may be applied to the surface of the packaging system at a position adjacent to the second end of the packaging system, so that this band may provide both the initial seal and re-closure of the packaging system. In such a case the adhesive or cold seal band may correspond to a region having a cohesive surface, i.e. a surface which will adhere only to another cohesive surface. Such re-closing means may also comprise spacers which will prevent unwanted adhesion. Such spacers are described in WO 95/13225, published on the 18th of May 1995. There may also be a plurality of spacers and a plurality of strips of adhesive material. The main requirement is that the communication between the exterior and the interior of the package should be minimal, even after first opening of the packaging system. A cold seal may be used, and in particular a grid of cold seal, whereby the cold seal is adapted so as to facilitate opening of the packaging system.

Examples

[0130] The following is a non-limiting example of a suitable perfume composition which is used in the following non-limiting detergent tablet examples according to the present invention:

Perfume Component	% in Perfume Composition
Geraniol	5.0
Citronellol	5.0
4 t-Butyl Cyclo Hexyl Acetate	5.0
Phenyl Ethyl Alcohol	10.0
Hexahydro-4,7-Methano-Inden-5-yl Acetate commercially available under the tradename Cyclacet	6.0
Citronellyl Acetate	2.5
Geranyl Acetate	2.5
Hexyl Cinnamic Aldehyde	4.5
Para Hydroxy Phenyl Butanone	3.0
PT Bucinal	24.0
Methyl Ionone	10.0

(continued)

Perfume Component	% in Perfume Composition
Rosalva	2.0
Methyl Dihydro Jasmonate	7.0
Undecylenic Aldehyde	0.5
Methyl Iso Butenyl Tetra Hydro Pyran	1.0
Ortho t Butyl Cyclo Hexyl Acetate	6.0
Hexyl Salicylate	6.0
Total	100.0

Abbreviations used in the following detergent Examples 1-6

[0131] In the detergent compositions, the abbreviated component identifications have the following meanings:

Anionic agglomerates 1 comprise of 40% anionic surfactant, 27% zeolite and 33% carbonate
 Anionic agglomerates 2 comprise of 40% anionic surfactant, 28% zeolite and 32% carbonate
 Nonionic agglomerate comprise 26% nonionic surfactant, 6% Lutensil K-HD 96, 40% Sodium acetate anhydrous, 20% carbonate and 8% zeolite.
 Cationic agglomerates comprise of 20% cationic surfactant, 56% zeolite and 24% sulphate
 Layered silicate comprises of 95% SKS 6 and 5% silicate
 Bleach activator agglomerates comprise of 81% TAED, 17% acrylic/maleic copolymer (acid form) and 2% water.
 Ethylene diamine N,N-disuccinic acid sodium salt/Sulphate particle comprise of 58% of Ethylene diamine N,N-disuccinic acid sodium salt, 23% of sulphate and 19% water.
 Suds suppressor comprises of 11.5% silicone oil (ex Dow Corning); 59% of zeolite and 29.5% of water.
 Blinder spray-on system comprises 16% by weight of polymer of the following kind:



68 % by weight of: PEG4000 and 16% by weight of: DIBS (Sodium di isoalkylbenzene sulphonate or Sodium toluene sulphonate).

Abbreviations used in the following detergent Examples 7

[0132] In the detergent compositions, the abbreviated component identifications have the following meanings:

LAS	Sodium linear C ₁₁₋₁₃ alkyl benzene sulfonate
TAS	Sodium tallow alkyl sulfate
CxyAS	Sodium C _{1x} - C _{1y} alkyl sulfate
C46SAS	Sodium C ₁₄ - C ₁₆ secondary (2,3) alkyl sulfate
CxyEzS	Sodium C _{1x} -C _{1y} alkyl sulfate condensed with z moles of ethylene oxide
CxyEz	C _{1x} -C _{1y} predominantly linear primary alcohol condensed with an average of z moles of ethylene oxide
QAS	R ₂ -N ⁺ (CH ₃) ₂ (C ₂ H ₄ OH) with R ² = C ₁₂ - C ₁₄
QAS 1	R ₂ -N ⁺ (CH ₃) ₂ (C ₂ H ₄ OH) with R ² = C ₈ - C ₁₁
SADS	Sodium C ₁₄ -C ₂₂ alkyl disulfate of formula 2-(R).C ₄ H ₇ -1,4-(SO ₄ ⁻) ₂ where R = C ₁₀ -C ₁₈
SADE2S	Sodium C ₁₄ -C ₂₂ alkyl disulfate of formula 2-(R).C ₄ H ₇ -1,4-(SO ₄ ⁻) ₂ where R = C ₁₀ -C ₁₈ , condensed with z moles of ethylene oxide

(continued)

	MES	x-sulpho methylester of C ₁₈ fatty acid
	APA	C ₈ - C ₁₀ amido propyl dimethyl amine
5	Soap	Sodium linear alkyl carboxylate derived from an 80/20 mixture of tallow and coconut fatty acids
	STS	Sodium toluene sulphonate
	CFAA	C ₁₂ -C ₁₄ (coco) alkyl N-methyl glucamide
	TFAA	C ₁₆ -C ₁₈ alkyl N-methyl glucamide
10	TPKFA	C ₁₆ -C ₁₈ topped whole cut fatty acids
	STPP	Anhydrous sodium tripolyphosphate
	TSPP	Tetrasodium pyrophosphate
15	Zeolite A	Hydrated sodium aluminosilicate of formula Na ₂ (Al ₁ O ₂ SiO ₂) ₁₂ ·27H ₂ O having a primary particle size in the range from 0.1 to 10 micrometers (weight expressed on an anhydrous basis)
	NaSKS-6	Crystalline layered silicate of formula δ-Na ₂ Si ₂ O ₅
	Citric acid	Anhydrous citric acid
	Borate	Sodium borate
20	Carbonate	Anhydrous sodium carbonate with a particle size between 200µm and 900µm
	Bicarbonate	Anhydrous sodium bicarbonate with a particle size distribution between 400µm and 1250µm
	Silicate	Amorphous sodium silicate (SiO ₂ :Na ₂ O = 2.0:1)
	Sulfate	Anhydrous sodium sulfate
25	Mg sulfate	Anhydrous magnesium sulfate
	Citrate	Tri-sodium citrate dihydrate of activity 86.4% with a particle size distribution between 425µm and 850µm
	MA/AA	Copolymer of 1:4 maleic/acrylic acid, average molecular weight about 70,000
	MA/AA (1)	Copolymer of 4:6 maleic/acrylic acid, average molecular weight about 10,000
30	AA	Sodium polyacrylate polymer of average molecular weight 4,500
	CMC	Sodium carboxymethyl cellulose
	Cellulose ether	Methyl cellulose ether with a degree of polymerization of 850 available from Shin Etsu Chemicals
35	Protease	Proteolytic enzyme, having 3.3% by weight of active enzyme, sold by NOVO Industries A/S under the tradename Savinase
	Protease I	Proteolytic enzyme, having 4% by weight of active enzyme, as described in WO 95/10591, sold by Genencor int. Inc.
	Alcalase	Proteolytic enzyme, having 5.3% by weight of active enzyme, sold by NOVO Industries A/S
40	Cellulase	Cellulytic enzyme, having 0.23% by weight of active enzyme, sold by NOVO Industries A/S under the tradename Carezyme
	Amylase	Amylolytic enzyme, having 1.6% by weight of active enzyme, sold by NOVO Industries A/S under the tradename Termamyl 120T
	Amylase II	Amylolytic enzyme, as disclosed in PCT/US9703635
45	Lipase	Lipolytic enzyme, having 2.0% by weight of active enzyme, sold by NOVO Industries A/S under the tradename Lipolase
	Lipase II	Lipolytic enzyme, having 2.0% by weight of active enzyme, sold by NOVO Industries A/S under the tradename Lipolase Ultra
50	Endolase	Endoglucanase enzyme, having 1.5% by weight of active enzyme, sold by NOVO Industries A/S
	PB4	Sodium perborate tetrahydrate of nominal formula NaBO ₂ ·3H ₂ O·H ₂ O ₂
	PB1	Anhydrous sodium perborate bleach of nominal formula NaBO ₂ ·H ₂ O ₂
	Percarbonate	Sodium percarbonate of nominal formula 2Na ₂ CO ₃ ·3H ₂ O ₂
55	DOBS	Decanoyl oxybenzene sulfonate in the form of the sodium salt
	DPDA	Diperoxidodecanedioic acid
	NOBS	Nonanoyloxybenzene sulfonate in the form of the sodium salt
	NACA-OBS	(6-nonamidocaproyl) oxybenzene sulfonate

(continued)

LOBS	Dodecanoyloxybenzene sulfonate in the form of the sodium salt
DOBS	Decanoyloxybenzene sulfonate in the form of the sodium salt
5 DOBA	Decanoyl oxybenzoic acid
TAED	Tetraacetylenetriethylenediamine
DTPA	Diethylene triamine pentaacetic acid
DTPMP	Diethylene triamine penta (methylene phosphonate), marketed by Monsanto under the Tradename Dequest 2060
10 EDDS	Ethylenediamine-N,N'-disuccinic acid, (S,S) isomer in the form of its sodium salt.
Photoactivated	Sulfonated zinc phthiocyanine encapsulated in bleach (1) dextrin soluble polymer
Photoactivated	Sulfonated aluminophthiocyanine encapsulated in bleach (2) dextrin soluble polymer
Brightener 1	Disodium 4,4'-bis(2-sulphostyryl)biphenyl
15 Brightener 2	Disodium 4,4'-bis(4-anilino-6-morpholino-1,3,5-triazin-2-yl)amino stilbene-2,2'-disulfonate
HEDP	1,1-hydroxyethane diphosphonic acid
PEGx	Polyethylene glycol, with a molecular weight of x (typically 4,000)
PEO	Polyethylene oxide, with an average molecular weight of 50,000
20 TEPAE	Tetraethylenepentaamine ethoxylate
PVI	Polyvinyl imidazole, with an average molecular weight of 20,000
PVP	Polyvinylpyrrolidone polymer, with an average molecular weight of 60,000
PVNO	Polyvinylpyridine N-oxide polymer, with an average molecular weight of 50,000
25 PVPVI	Copolymer of polyvinylpyrrolidone and vinylimidazole, with an average molecular weight of 20,000
QEA	$\text{bis}[(\text{C}_2\text{H}_5\text{O})(\text{C}_2\text{H}_4\text{O})_n](\text{CH}_3)^-\text{N}^+-\text{C}_6\text{H}_{12}-\text{N}^+(\text{CH}_3)^-\text{bis}[(\text{C}_2\text{H}_5\text{O})-(\text{C}_2\text{H}_4\text{O})_n]$, wherein n = from 20 to 30
30 PEI	Polyethyleneimine with an average molecular weight of 1800 and an average ethoxylation degree of 7 ethyleneoxy residues per nitrogen
Clay I	Bentonite clay
Clay II	Smectite clay
Flocculating agent I	polyethylene oxide of average molecular weight of between 200,000 and 400,000
Flocculating agent II	polyethylene oxide of average molecular weight of between 400,000 and 1,000,000
35 Flocculating agent III	polymer of acrylamide and/ or acrylic acid of average molecular weight of 200,000 and 400,000
SRP I	Anionically end-capped polyester soil release polymer
SRP II	Polysaccharide soil release polymer
40 SRP 1	Nonionically end capped poly esters
SRP 2	Diethoxylated poly (1, 2 propylene terephthalate) short block polymer
Silicone antifoam	Polydimethylsiloxane foam controller with siloxane-oxyalkylene copolymer as dispersing agent with a ratio of said foam controller to said dispersing agent of 10:1 to 100:1
Opacifier	Water based monostyrene latex mixture, sold by BASF Aktiengesellschaft under the tradename Lytron 521
45 Wax	Paraffin wax
Speckle	Coloured carbonate salt or organic carboxylic acid / salt

Example 1**[0133]**

I) A detergent base powder of composition A was prepared as follows: all the particulate material of base composition were mixed together in a mixing drum or spray drum to form a homogenous particulate mixture, apart from the binder spray-on system, the fluorescer or brightener, and the photobleach Zinc Phthalocyanine sulphonate. The particulate mixture was thereafter divided in two equal parts, one part for making a white layer, another part for making a green layer. The white layer material is obtained by spraying the brightener or fluorescer together

with half of the binder. The green layer material is obtained by spraying the photobleach Zinc Phthalocyanine sulphonate together with the rest of the binder. The layer where then processed independently in a Loedige KM 600®.

ii) Using a Bonals® rotary press both matrices were filled in two independent force feeding flasks. Both layers are compressed together in the precompression and compression stations to form a dual layer tablet.

iii) In this particular example, the tablets have a square cross section of 45 mm side, a height of 24 mm and a weight of 45 gr. The height of the green bottom layer corresponded to 50% of the total height of the tablet. The tensile strength of the uncoated tablets was 13 kpa.

iv) The tablet was thereafter coated with 2.5 g of coating formed from 90% by weight of adipic acid and 10% by weight of Bentonite clay from CSM.

	Composition A	
	(%)	
Anionic agglomerates 1		9.1
Anionic agglomerates 2		22.5
Nonionic agglomerates		9.1
Cationic agglomerates		4.6
Layered silicate		9.7
Sodium percarbonate		12.2
Bleach activator agglomerates		6.1
Sodium carbonate		7.67
EDDS/Sulphate particle		0.5
Tetrasodium salt of Hydroxyethane Diphosphonic acid		0.6
Soil Release Polymer		0.3
Fluorescer		0.2
Zinc Phthalocyanine sulphonate		0.03
Soap powder		1.2
Suds suppressor		2.8
Citric acid		5.5
Protease		1
Lipase		0.35
Cellulase		0.2
Amylase		1.1
Binder spray-on system		4.75
Perfume spray-on		0.5

Example 2

[0134]

i) A detergent base powder of composition A was prepared as follows: all the particulate material of base composition was mixed together in a mixing drum or spray drum to form a homogenous particulate mixture. The binder system was then sprayed on. The powder where then processed in a Loedige KM 600®.

ii) Using a Instron® Laboratory bench press, detergent powder was filled in the die. The powder had been compressed with a force so that the tensile strength of the tablet was 10kpa.

iii) In this particular example, the tablets have a diameter of 54 mm side, a height of 24 mm and a weight of 45 gr.

iv) The tablet was thereafter coated with 2.5 g of coating formed from 90% by weight of Adipic acid and 10% by

weight of bentonite clay from CSM.

Example 3

[0135]

- i) A detergent base powder of composition A was prepared as follows: all the particulate material of base composition were mixed together in a mixing drum or spray drum to form a homogenous particulate mixture. The binder system was then sprayed on. The powder where then processed in a Loedige KM 600®.
- ii) Using a Instron® Laboratory bench press, detergent powder was filled in the die. The powder had been compressed with a force so that the tensile strength of the tablet was 10kpa.
- iii) In this particular example, the tablets have a diameter of 54 mm side, a height of 24 mm and a weight of 45 gr.

The tablet was thereafter coated with 2.5 g of coating formed from 89% by weight of Adipic acid, 10% by weight of bentonite clay from and 1% by weight of Coasol™.

Example 4

[0136]

- i) A detergent base powder of composition A was prepared as follows: all the particulate material of base composition were mixed together in a mixing drum or spray drum to form a homogenous particulate mixture. The binder system was then sprayed on. The powder where then processed in a Loedige KM 600®.
- ii) Using a Instron® Laboratory bench press, detergent powder was filled in the die. The powder had been compressed with a force so that the tensile strength of the tablet was 10kpa.
- iii) In this particular example, the tablets have a diameter of 54 mm side, a height of 24 mm and a weight of 45 gr.

The tablet was thereafter coated with 2.5 g of coating formed from 87% by weight of Adipic acid, 10% by weight of bentonite clay from and 1% of Coasol™ and 2 % of Solka-Floc™ 1016.

Example 5

[0137]

- i) A detergent base powder of composition A was prepared as follows: all the particulate material of base composition were mixed together in a mixing drum or spray drum to form a homogenous particulate mixture. The binder system was then sprayed on. The powder where then processed in a Loedige KM 600®.
- ii) Using a Instron® Laboratory bench press, detergent powder was filled in the die. The powder had been compressed with a force so that the tensile strength of the tablet was 10kpa.
- iii) In this particular example, the tablets have a diameter of 54 mm side, a height of 24 mm and a weight of 45 gr.

The tablet was thereafter coated with 2.5 g of coating formed from 78% by weight of Adipic acid, 18.5% by weight of bentonite clay from and 1% by weight of Coasol™ and 2.5 % by weight of NaOH (1M).

Example 6

[0138]

- i) A detergent base powder of composition A was prepared as follows: all the particulate material of base composition were mixed together in a mixing drum or spray drum to form a homogenous particulate mixture. The binder system was then sprayed on. The powder where then processed in a Loedige KM 600®.
- ii) Using a Instron® Laboratory bench press, detergent powder was filled in the die. The powder had been compressed with a force so that the tensile strength of the tablet was 10kpa.
- iii) In this particular example, the tablets have a diameter of 54 mm side, a height of 24 mm and a weight of 45 gr.

The tablet was thereafter coated with 2.5 g of coating formed from 88% by weight of Adipic acid, 10% by weight of bentonite clay from and 1% by weight of Coasol™ and 1 % by weight of tetrasodium salt of ethane 1-hydroxy diphosphate.

Example 7

[0139] The following are detergent compositions according to the invention which may be used as is or in place of Composition A, above described, in any one of Examples 1-6.

[0140] In the following examples all levels are quoted as % by weight of the composition:

		B	C	D	E
	Blown powder				
	Clay I or II	7.0	10.0	6.0	2.0
	Flocculating agent I or II	0.3	1.0	1.0	0.5
	LAS	16.0	5.0	11.0	6.0
	TAS	-	5.0	-	2.0
	Zeolite A	-	20.0	-	10.0
	STPP	24.0	-	14.0	-
	Sulfate	-	2.0	-	-
	MA/AA	-	2.0	1.0	1.0
	Silicate	4.0	7.0	3.0	-
	CMC	1.0	-	0.5	0.6
	Brightener	0.2	0.2	0.2	0.2
	Sodium carbonate	10.0	10.0	20.0	-
	DTPMP	0.4	0.4	0.2	-
	Spray on				
	Brightener	0.02	-	-	0.02
	C45E7 or E9	-	-	2.0	1.0
	C45E3 or E4	-	-	2.0	4.0
	Perfume	0.5	-	0.5	0.2
	Silicone antifoam	0.3	-	-	-
	Dry additives				
	QEA	-	-	-	1.0
	HEDP/EDDS	0.3	-	-	-
	Sulfate	2.0	-	-	-
	Carbonate	20.0	13.0	15.0	24.0
	Citric acid	2.5	-	-	2.0
	QAS	-	-	0.5	0.5
	SKS-6	3.5	-	-	5.0
	Percarbonate	-	-	-	9.0
	PB4	-	-	5.0	-
	NOBS	-	-	-	1.3
	TAED	-	-	2.0	1.5
	Protease	1.0	1.0	1.0	1.0
	Lipase	-	0.4	-	0.2
	Amylase	0.2	0.2	0.2	0.4

(continued)

		B	C	D	E
	Brightener	0.05	-	-	0.05
	Perfume	1.0	0.2	0.5	0.3
	Speckle	1.2	0.5	2.0	-
	Misc/minor to 100%				

[0141] The following are compositions suitable for use herein

	F	G	H	I	J	K	L
Sodium C ₁₁ -C ₁₃ alkylbenzenesulfonate	12.0	16.0	23.0	19.0	18.0	20.0	16.0
Sodium C ₁₄ -C ₁₅ alcohol sulfate		4.5	-	-	-	-	4.0
C ₁₄ -C ₁₆ alcohol ethoxylate (0.5) sulfate			-	-	-	-	-
C ₁₄ -C ₁₆ alcohol ethoxylate (3) sulfate	-	-	2.0	-	1.0	1.0	1.0
Sodium C ₁₄ -C ₁₅ alcohol ethoxylate	2.0	2.0	-	1.3	-	-	5.0
C ₉ -C ₁₄ alkyl dimethyl hydroxy ethyl quaternary ammonium salt			-	-	1.0	0.5	2.0
Tallow fatty acid			-	-	-	-	1.0
Tallow alcohol ethoxylate (50)	-	-	-	-	-	-	-
Sodium tripolyphosphate / Zeolite	23.0	25.0	14.0	22.0	20.0	10.0	20.0
Sodium carbonate	25.0	22.0	35.0	20.0	28.0	41.0	30.0
Sodium Polyacrylate (45%)	0.5	0.6	0.6	0.5	-	-	-
Sodium polyacrylate/maleate polymer	-	-	1.0	1.0	1.0	2.0	0.5
Sodium silicate (1.6 ratio NaO/SiO ₂) (46%)	3.0	6.0	9.0	8.0	9.0	6.0	8.0
Sodium sulfate	-	-	-	-	-	2.0	3.0
Sodium perborate/percarbonate	5.0	5.0	10.0	-	3.0	1.0	-
Poly(ethyleneglycol), MW ~4000 (50%)	1.5	1.5	1.0	1.0	-	-	0.5
Sodium carboxy methyl cellulose	1.0	1.0	1.0	-	0.5	0.5	0.5
Citric acid	-	-	-	-	-	-	-
NOBS/ DOBS	-	1.0	-	-	1.0	0.7	-
TAED	1.5	1.0	2.5	-	3.0	0.7	-
SRP	1.5	1.5	1.0	1.0	-	1.0	-
Clay I or II	5.0	6.0	12.0	7.0	10.0	4.0	3.0
Flocculating agent I or III	0.2	0.2	3.0	2.0	0.1	1.0	0.5
Humectant	0.5	1.0	0.5	1.0	0.5	0.5	-
Wax	0.5	0.5	1.0	-	-	0.5	0.5
Moisture	7.5	7.5	6.0	7.0	5.0	3.0	5.0
Magnesium sulphate	-	-	-	-	-	0.5	1.5
Chelant	-	-	-	-	0.8 0.6		1.0
Enzymes, including amylase cellulase, protease and lipase	-	-	-	-	2.0	1.5	2.0

(continued)

	F	G	H	I	J	K	L
Speckle	2.5	4.1	4.2	4.4	5.6	5.0	5.2
minors, e.g. perfume, PVP, PVPV/PVNO, brightener, photo-bleach,	2.0	1.0	1.0	1.0	2.5	1.5	1.0

[0142] The following are detergent compositions suitable for use herein

	M	N	O	P
Sodium C ₁₁ -C ₁₃ alkylbenzenesulfonate	23.0	13.0	20.0	18.0
Sodium C ₁₄ -C ₁₅ alcohol sulfate	-	4.0	-	-
Clay I or II	5.0	10.0	14.0	6.0
Flocculating agent I or II	0.2	0.3	0.1	0.9
Wax	0.5	0.5	1.0	-
Humectant (glycerol/ silica)	0.5	2.0	1.5	-
C ₁₄ -C ₁₅ alcohol ethoxylate sulfate	-	-	-	2.0
Sodium C ₁₄ -C ₁₅ alcohol ethoxylate (2.5	3.5	-	-
C ₈ -C ₁₄ alkyl dimethyl hydroxy ethyl quaternary ammonium salt	-	-	-	0.5
Tallow fatty acid	0.5	-	-	-
Tallow alcohol ethoxylate (50)	-	-	-	1.3
Sodium tripolyphosphate	-	41.0	-	20.0
Zeolite A, hydrate (0.1-10 micron size)	26.3	-	21.3	-
Sodium carbonate	24.0	22.0	35.0	27.0
Sodium Polyacrylate (45%)	2.4	-	2.7	-
Sodium polyacrylate/maleate polymer	-	-	1.0	2.5
Sodium silicate (1.6 or 2 or 2.2 ratio NaO/SiO ₂)(46%)	4.0	7.0	2.0	6.0
Sodium sulfate	-	6.0	2.0	-
Sodium perborate/ percarbonate	8.0	4.0	-	12.0
Poly(ethyleneglycol), MW ~4000 50%)	1.7	0.4	1.0	-
Sodium carboxy methyl cellulose	1.0	-	-	0.3
Citric acid	-	-	3.0	-
NOBS/DOBS	1.2	-	-	1.0
TAED	0.6	1.5	-	3.0
Perfume	0.5	1.0	0.3	0.4
Soil release polymer	-	1.5	1.0	1.0
Moisture	7.5	3.1	6.1	7.3
Magnesium sulphate	-	-	-	1.0
Chelant	-	-	-	0.5
speckle	1.0	0.5	0.2	2.7
Enzymes, including amylase, cellulase, protease and lipase	-	1.0	-	1.5
minors, e.g. brightener, photo-bleach	1.0	1.0	1.0	1.0

EP 1 035 198 A2

[0143] The following are detergent compositions suitable for use herein

		Q	R	S	T	U
5	Blown Powder					
	STPP/Zeolite A	9.0	15.0	15.0	9.0	9.0
	Flocculating agent II or III	0.5	0.2	0.9	1.5	-
	LAS	7.5	23.0	3.0	7.5	7.5
10	QAS	2.5	1.5	-	-	-
	DTPMP	0.4	0.2	0.4	0.4	0.4
	HEDP or EDDS	-	0.4	0.2	-	-
15	CMC	0.1	0.4	0.4	0.1	0.1
	Sodium carbonate	5.0	20.0	20.0	10.0	-
	Brightener	0.05	-	-	0.05	0.05
	Clay I or II	-	10.0	-	-	-
20	STS	0.5	-	-	0.5	0.5
	MA/AA	1.5	2.0	2.0	1.5	1.5
	Agglomerates					
25	Suds suppresser (silicon)	1.0	1.0	-	2.0	0.5
	Agglomerate					
	Clay	9.0	-	-	4.0	10.0
30	Wax	0.5	-	-	0.5	1.5
	Glycerol	0.5	-	-	0.5	0.5
	Agglomerate					
	LAS	-	5.0	5.0	-	-
35	TAS	-	2.0	1.0	-	-
	Silicate	-	3.0	4.0	-	-
	Zeolite A	-	8.0	8.0	-	-
40	Carbonate	-	8.0	4.0	-	-
	Spray On					
	Perfume	0.3	-	-	0.3	0.3
	C45E7 or E9	2.0	-	-	2.0	2.0
45	C25E3 or E4	2.0	-	-	2.0	2.0
	Dry additives					
	Citrate or citric acid	2.5	-	2.0	2.5	2.5
50	Clay I or II	-	5.0	5.0	-	-
	Flocculating agent I or II	-	-	-	-	0.2
	Bicarbonate	-	3.0	-	-	-
	Carbonate	15.0	-	-	25.0	31.0
55	TAED	1.0	2.0	5.0	1.0	-
	Sodium perborate or percarbonate	6.0	7.0	10.0	6.0	-

(continued)

		Q	R	S	T	U
	SRP I, II or III	0.2	0.1	0.2	0.5	0.3
	CMC or nonionic cellulose ether	1.0	1.5	0.5	-	-
	Protease	0.3	1.0	1.0	0.3	0.3
	Lipase	-	0.4	0.4	-	-
	Amylase	0.2	0.6	0.6	0.2	0.2
	Cellulase	0.2	0.6	0.6	0.2	0.2
	Silicone antifoam	-	5.0	5.0	-	-
	Perfume (starch)	0.2	0.3	1.0	0.2	0.2
	Speckle	0.5	0.5	0.1	-	1.0
	SKS-6 (silicate 2R)	3.5	-	-	-	3.5
	Photobleach	0.1	-	-	0.1	0.1
	Soap	0.5	2.5	-	0.5	0.5
	Sodium sulfate	-	3.0	-	-	-
	Misc/minors to 100%	100.0	100.0	100.0	100.0	100.0
	Density (g/litre)	850	850	850	850	850

Claims

1. A perfumed detergent tablet, the tablet comprising a clay mineral compound; and wherein the perfume comprises less than 0.6% of Schiff-base by weight of the perfume composition.
2. A perfumed detergent tablet according to Claim 1, wherein said tablet further comprises a coating.
3. A tablet according to either one of Claim 1 or 2, wherein the clay mineral compound is present in the coating in particles having a size below 75µm diameter.
4. A tablet according to any one of Claims 1-3, wherein the tablet is a softening tablet.
5. A tablet according to any one of Claims 1-4, wherein the perfume composition is essentially free of schiff bases.
6. A tablet according to any one of Claims 1-5, wherein the perfume composition is free of perfume ingredients selected from Methyl Anthranilate and HydroxyCitronellal; Methyl Anthranilate and Methyl Nonyl Acetaldehyde; Methyl Anthranilate and PT Bucinal; Methyl anthranilate and Lyral; Methyl Anthranilate and Ligustral; and mixtures thereof.
7. A tablet according to any one of Claims 2-6, wherein the coating further comprises an acid having a melting temperature of at least 40°C, preferably of at least 145°C.
8. A tablet according to Claim 7, wherein the acid having a melting temperature of at least 40°C has a crystallised structure.
9. A tablet according to claim 8, wherein the acid forming the crystallised structure is a dicarboxylic acid, preferably adipic acid.
10. A tablet according to any one of claims 2-9, wherein the coating consists essentially of adipic acid.
11. A tablet according to any one of Claims 2-10, wherein the coating further comprises a component which is liquid

at 25°C.

12. A tablet according to any one of Claims 2-11, wherein the coating further comprises reinforcing fibres.

13. A tablet according to any one of Claims 1-12, wherein the tablet further contains a heavy metal ion sequestrant, preferably selected from organic phosphonates.

14. A tablet according to any one of Claims 1-13, wherein the detergent composition further comprises a flocculating agent.

15. A process for making a tablet according to any one of Claims 2-14 comprising the steps of:

(a) forming a core by compressing a particulate material, the particulate material comprising surfactant and detergent builder;

(b) applying a coating material to the core, the coating material being in the form of a melt;

(c) allowing the molten coating material to solidify;

characterised in that the coating comprises a clay.

16. A process for making a tablet according to any one of Claims 2 to 14 comprising the steps of:

(a) forming a core by compressing a particulate material, the particulate material comprising surfactant and detergent builder;

(b) applying a coating material to the core, the coating material being dissolved in a solvent or water;

(c) allowing the solvent or water to evaporate;

characterised in that the coating comprises a clay.

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 035 198 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
03.01.2001 Bulletin 2001/01

(51) Int Cl.7: **C11D 17/00**, C11D 3/50,
C11D 3/12, C11D 3/20
// C11D3/36

(43) Date of publication A2:
13.09.2000 Bulletin 2000/37

(21) Application number: 99870081.9

(22) Date of filing: 30.04.1999

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

- Cunningham, Philip Andrew
Newcastle upon Tyne, NE12 9JN (GB)
- Green, Michael (NMN)
Newcastle upon Tyne, NE5 4SX (GB)
- McRitchie, Allan Campbell
Tyne & Wear, NE26 1SY (GB)

(30) Priority: 12.03.1999 EP 99870044

(71) Applicant: **THE PROCTER & GAMBLE COMPANY**
Cincinnati, Ohio 45202 (US)

(74) Representative: **Gault, Nathalie et al**
BVBA Procter & Gamble Europe Sprl
Temseleaan 100
1853 Strombeek-Bever (BE)

(72) Inventors:
• Arnau, José (NMN)
78180 Montigny-le-Brettonneux (FR)

(54) **Perfumed detergent tablet**

(57) The present invention relates to a perfumed detergent tablet, the tablet comprising a clay mineral com-

pound, and the perfume comprising less than 0.6% of Schiff-base by weight of the perfume composition.

EP 1 035 198 A3

European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 87 0081

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (MCL7)
E, D	EP 1 026 229 A (PROCTER & GAMBLE) 9 August 2000 (2000-08-09) * example 1 * * claims * * page 11, line 31 - line 32 * * page 14, line 14 - line 16 * * page 3, line 34 - page 4, line 26 * ----	1-16	C11D17/00 C11D3/50 C11D3/12 C11D3/20 //C11D3/36
E, D	EP 1 026 228 A (PROCTER & GAMBLE) 9 August 2000 (2000-08-09) * claims; example 1 * ----	1-16	
E, D	EP 1 026 227 A (PROCTER & GAMBLE) 9 August 2000 (2000-08-09) * claims; example 1 * ----	1-16	
D, X	EP 0 846 754 A (PROCTER & GAMBLE) 10 June 1998 (1998-06-10) * claims; example 1 * * page 4, line 3 - line 11 * ----	1-10, 13, 15, 16	
D, X	EP 0 846 755 A (PROCTER & GAMBLE) 10 June 1998 (1998-06-10) * claims; example 1 * * page 4, line 19 - line 27 * ----	1-10, 13, 15, 16	TECHNICAL FIELDS SEARCHED (MCL7) C11D
D, X	EP 0 846 756 A (PROCTER & GAMBLE) 10 June 1998 (1998-06-10) * claims; example 1 * ----	1-10, 13, 15, 16	
E	WO 99 27069 A (PROCTER & GAMBLE) 3 June 1999 (1999-06-03) * claims 1-8 * * page 64 - page 65 * * page 75 * ----	1-10, 13, 14	
-/-			
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 14 November 2000	Examiner Serbetsoglou, A
CATEGORY OF CITED DOCUMENTS T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application I : document cited for other reasons A : technological background N : non-written disclosure P : intermediate document X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category			

EPO FORM 1503 (3.05.99) (EN)

European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 87 0081

DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim
E	WO 99 31215 A (PROCTER & GAMBLE) 24 June 1999 (1999-06-24) * page 50 - page 53 * * claims; examples *	1, 13, 14
X	WO 99 06521 A (PROCTER & GAMBLE) 11 February 1999 (1999-02-11) * claim 1; example 1 * * page 57, line 28 - line 29 * * page 55, line 9 - line 16 * * page 53, line 14 - line 26 *	1, 13, 14
X	WO 95 20030 A (UNILEVER PLC) 27 July 1995 (1995-07-27) * examples 1, 4 * * claims 1-13, 27-34 *	1
A	WO 97 05226 A (PROCTER & GAMBLE) 13 February 1997 (1997-02-13) * claims 1-3 *	1, 13
E	WO 99 40171 A (UNILEVER PLC) 12 August 1999 (1999-08-12) * page 12, line 11 - page 13, line 25 * * page 24, line 5 - page 25, line 3 * * claims 1-8 *	1
		TECHNICAL FIELDS SEARCHED (INCL)
The present search report has been drawn up for all claims		
Place of search	Date of completion of the search	Examiner
THE HAGUE	14 November 2000	Serbetsoglou, A
CATEGORY OF CITED DOCUMENTS X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background Q: non-written disclosure P: intermediate document T: theory or principle underlying the invention E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons &: member of the same patent family, corresponding document		

EPO FORM 1800 (01/97) (P/INT)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 87 0081

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

14-11-2000

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
EP 1026229	A	09-08-2000	WO	0046340 A	10-08-2000
EP 1026228	A	09-08-2000	WO	0046339 A	10-08-2000
EP 1026227	A	09-08-2000	WO	0046338 A	10-08-2000
EP 0846754	A	10-06-1998	AU	7625098 A	29-06-1998
			BR	9713992 A	08-02-2000
			CN	1245528 A	23-02-2000
			WO	9824874 A	11-06-1998
			US	6067311 A	11-07-2000
EP 0846755	A	10-06-1998	AU	5443898 A	29-06-1998
			BR	9714379 A	21-03-2000
			CN	1245529 A	23-02-2000
			WO	9824875 A	11-06-1998
EP 0846756	A	10-06-1998	AU	5443698 A	29-06-1998
			BR	9713871 A	14-03-2000
			CN	1245527 A	23-02-2000
			WO	9824873 A	11-06-1998
WO 9927069	A	03-06-1999	EP	1034250 A	13-09-2000
WO 9931215	A	24-06-1999	GB	2332442 A	23-06-1999
			BR	9813815 A	03-10-2000
			EP	1047764 A	02-11-2000
WO 9906521	A	11-02-1999	GB	2327947 A	10-02-1999
			EP	0998552 A	10-05-2000
WO 9520030	A	27-07-1995	AU	702040 B	11-02-1999
			AU	1575695 A	08-08-1995
			BR	9506561 A	28-10-1997
			CA	2180433 A	27-07-1995
			DE	69502701 D	02-07-1998
			DE	69502701 T	26-11-1998
			EP	0741776 A	13-11-1996
			ES	2118561 T	16-09-1998
WO 9705226	A	13-02-1997	ZA	9500587 A	25-07-1996
			GB	2303635 A	26-02-1997
			AU	6636696 A	26-02-1997
			CA	2227772 A	13-02-1997
			EP	0847438 A	17-06-1998
			JP	11510532 T	14-09-1999

EPO Patent Index

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 87 0081

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

14-11-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9705226 A		US 6063747 A	16-05-2000
WO 9940171 A	12-08-1999	AU 2720699 A	23-08-1999

EPO/COM/Paris

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

